

AHU Model		AHU18-SG2	AHU24-SG2	AHU30-SG2	AHU36-SG2	AHU48-SG2	AHU60-SG2	
Power supply	V- Ph-Hz	208/230V,1Ph, 60Hz	208/230V,1Ph, 60Hz	208/230V,1Ph, 60Hz	208/230V,1Ph, 60Hz	208/230V,1Ph, 60Hz	208/230V,1Ph, 60Hz	
MINIMUM CIRCUIT AMPACITY(Indoor)	A	3	4	4.5	4.5	4.5	7	
MAX.FUSE(Indoor)	A	15	15	15	15	15	15	
Indoor fan motor	Model	ZKFD-250-8-1	ZKFD-250-8-1	ZKFD-375-8-1	ZKFD-375-8-1	ZKFD-560-8-1	ZKFD-750-8-1	
	RLA	A	1	3	3.5	3.5	5	
Indoor air flow (Hi/Mi/Lo)	m3/h	980/900/830	1290/1180/1070	1520/1370/1210	1840/1650/1470	2180/1860/1540	2690/2310/1930	
Indoor air flow (Hi/Mi/Lo)	CFM	576.47/529.41/488.24	758.82/694.12/629.41	894.12/805.88/711.76	1082.35/970.59/864.71	1282.35/1094.12/905.88	1582.35/1358.82/1135.29	
ESP	Range	Pa	0-200	0-200	0-200	0-200	0-200	
	Range	In. wg.	0-0.8	0-0.8	0-0.8	0-0.8	0-0.8	
Indoor noise level (Hi/Mi/Lo)	dB(A)	36/34/32	43/40/35.5	43/40/30.5	46.8/44/41.3	53/50/46	52.5/49/44	
Throttle type	/	EXV	EXV	EXV	EXV	EXV	EXV	
Indoor unit	Dimension(W*D*H)	mm	445*534*1143	445*534*1143	534*534*1245	534*534*1245	534*534*1245	622*534*1346
	Dimension(W*D*H)	inch	21*17-1/2*45	21*17-1/2*45	21.*21*49	21.*21*49	21.*21*49	24-1/2*x21*53
	Packing (W*D*H)	mm	640x530x1280	640x530x1280	640x620x1380	640x620x1380	640x620x1380	640x705x1480
	Packing (W*D*H)	inch	25.20x20.87x50.39	25.20x20.87x50.39	25.20x24.41x54.33	25.20x24.41x54.33	25.20x24.41x54.33	25.20x27.76x58.27
	Net/Gross weight	Kg	48/58.7	48/58.7	58.6/70.6	58.6/70.6	58.6/70.6	73.8/86.5
Net/Gross weight	lbs.	105.82/129.41	105.82/129.41	129.2/155.6	129.2/155.6	129.2/155.6	162.7/190.7	