

Sale Model		AHH24-410	AHH36-410	AHH48-410	AHH60-410
Indoor motor	Type		ECM	ECM	ECM
	Rated HP		1/3	1/2	3/4
	Rated RPM	r/min	1050	1050	1050
	FLA		2.8	4.1	6.0
Indoor fan	material		galvanized plate	galvanized plate	galvanized plate
	Type		centrifugal	centrifugal	centrifugal
	Diameter	inch	10-5/8	11	11
	Height	inch	8	10-5/8	10-5/8
Indoor coil	Number of rows		4*2	4*2	5*2
	Tube outside dia.and type		7mm/innergroove tube	7mm/innergroove tube	7mm/innergroove tube
	Fin spacing /thickness/type	mm/mm	1.6/0.095/hydrophilic aluminium	1.6/0.095/hydrophilic aluminium	1.6/0.095/hydrophilic aluminium
Tube pitch(a)x row pitch(b)	mm	13.37/21	13.37/21	13.37/21	
Indoor limit value of static pressure and air flow	Pa/CFM	25/800	37.5/1180	50/1560	50/1700
Indoor sound level (sound power level)	dB(A)	63	65	67	68
Metering device	Throttle type		TXV	TXV	TXV
	Model number		3TR	3TR	4TR
Electrical Data	Voltage-Phase-Hz	V-Ph-Hz	208/230V 1Ph 60Hz	208/230V 1Ph 60Hz	208/230V 1Ph 60Hz
	Minimum Circuit Ampacity		3.5	5.1	7.5
	Max. Overcurrent Protection		15	15	15
	Min/Max Volts		187 / 253	187 / 253	187 / 253
Indoor unit	Dimension (W*H*D)	mm	500x1180x550	560x1385x610	560x1385x610
		inch	19-5/8"x46-1/2"x21-5/8"	22"x54-1/2"x24"	22"x54-1/2"x24"
	Packing (W*H*D)	mm	644x1205x567	704x1410x627	704x1410x627
		inch	22-3/5"x47-4/5"x22-7/10"	27-7/10"x55-4/5"x25"	27-7/10"x55-4/5"x25"
	Net/Gross weight	kg	54/60	74/82	74/82
		lbs	119/132	161/178	162/180
Refrigerant piping Liquid side/ Gas side	inch	3/8 3/4	3/8 3/4	3/8 7/8	
Shipping per STD40HQ		154	104	104	