

Sale Model			MRH24-410	MRH36-410	MRH48-410	MRH60-410
Cooling	Capacity	Btu/h	24000	34600	47000	57000
	EER	Btu/h.W	11.6	11.6	12	11.2
	SEER	Btu/h.W	17.5	17.5	17.5	17.5
Heating	Capacity	Btu/h	23800	33600	46500	55000
	HSPF	Btu/h.W	9.5	9.5	9.5	9.5
Compressor	Type		Rotary	Rotary	Rotary	Rotary
	Supplier		Mitsubishi	Mitsubishi	GMCC	GMCC
	RLA		13.5	18.5	23.5	27.2
	LRA		45	45	52	52
Fan Motor	Type		PSC	PSC	DC	DC
	Rated HP		1/8	1/6	1/3	1/3
	Capacitor	uF	6	6	/	/
	Rated RPM	r/min	1075	825	1050	1050
	FLA		0.8	1	2.5	2.5
Outdoor Fan	material		Metal	Metal	Metal	Metal
	Type		Axial flow	Axial flow	Axial flow	Axial flow
	Diameter	inch	23-5/8	23-5/8	23-5/8	23-5/8
	Height	inch	2-3/4	4-1/2	4-1/2	4-1/2
	Air flow	CFM	2400	2950	4100	4100
Condenser Coil	Number of rows		1	2	2	2
	Tube outside dia	mm(inch)	7(9/32)	7(9/32)	7(9/32)	7(9/32)
Electrical Data	Voltage-Phase-Hz	V-Ph-Hz	208/230V-1Ph-60Hz	208/230V-1Ph-60Hz	208/230V-1Ph-60Hz	208/230V-1Ph-60Hz
	Minimum Circuit Ampacity		17.7	24.2	31.9	36.5
	Max. Overcurrent Protection		30	40	50	60
	Min/Max Volts		187 / 253	187 / 253	187 / 253	187 / 253
Outdoor sound level (sound power level)			75	77	79	79
Outdoor unit	Dimension (W×H×D)	mm	740×633×740	740×633×740	740×843×740	740×843×740
		inch	29-1/8×24-15/16×29-1/8	29-1/8×24-15/16×29-1/8	29-1/8×33-3/16×29-1/8	29-1/8×33-3/16×29-1/8
	Packing (W×H×D)	mm	768×667×768	768×667×768	768×877×768	768×877×768
		inch	30-1/5×26-1/4×30-1/5	30-1/5×26-1/4×30-1/5	30-1/5×34-1/2×30-1/5	30-1/5×34-1/2×30-1/5
	Net/Gross weight	kg	65/69	71/75	91/96	91/96
		lbs	143/152	157/165	201/211	201/211
Refrigerant system	Liquid side/ Gas side	inch	3/8 / 3/4	3/8 / 3/4	3/8 / 7/8	3/8 / 7/8
	Factory charge R410A	oz	85	114	159	166
	Metering device		EEV	EEV	EEV	EEV
Operating temperatures	°F	5-120	5-120	5-120	5-120	
Maximum line length	Feet	100	100	100	100	
Maximum elevation difference	Feet	50	50	50	50	
Shipping per STD40HQ		180	180	135	135	