

Sale Model			MRR24-410	MRR36-410	MRR48-410	MRR60-410
Cooling	Capacity	Btu/h	24000	35200	48000	58000
	EER	Btu/h.W	12.5	12.2	12.5	11.7
	SEER	Btu/h.W	18	18	18	18
Heating	Capacity	Btu/h	/	/	/	/
	HSPF	Btu/h.W	/	/	/	/
Compressor	Type		Rotary	Rotary	Rotary	Rotary
	Supplier		Mitsubishi	Mitsubishi	GMCC	GMCC
	RLA		13.5	18.5	23.5	27.2
	LRA		45	45	52	52
Fan Motor	Type		PSC	PSC	DC	DC
	Rated HP		1/8	1/6	1/3	1/3
	Capacitor	uF	6	6	/	/
	Rated RPM	r/min	1075	825	1050	1050
	FLA		0.8	1	2.5	2.5
Outdoor Fan	material		Metal	Metal	Metal	Metal
	Type		Axial flow	Axial flow	Axial flow	Axial flow
	Diameter	inch	23-5/8	23-5/8	23-5/8	23-5/8
	Height	inch	2-3/4	4-1/2	4-1/2	4-1/2
	Air flow	CFM	2400	2950	4100	4100
Condenser Coil	Number of rows		1	2	2	2
	Tube outside dia	mm(inch)	7(9/32)	7(9/32)	7(9/32)	7(9/32)
Electrical Data	Voltage-Phase-Hz	V-Ph-Hz	208/230V-1Ph-60Hz	208/230V-1Ph-60Hz	208/230V-1Ph-60Hz	208/230V-1Ph-60Hz
	Minimum Circuit Ampacity		17.7	24.2	31.9	36.5
	Max. Overcurrent Protection		30	40	50	60
	Min/Max Volts		187 / 253	187 / 253	187 / 253	187 / 253
Outdoor sound level (sound power level)			75	77	79	79
Outdoor unit	Dimension (W×H×D)	mm	740×633×740	740×633×740	740×843×740	740×843×740
		inch	29-1/8×24-15/16×29-1/8	29-1/8×24-15/16×29-1/8	29-1/8×33-3/16×29-1/8	29-1/8×33-3/16×29-1/8
	Packing (W×H×D)	mm	768X667X768	768X667X768	768X877X768	768X877X768
		inch	30-1/5x26-1/4x30-1/5	30-1/5x26-1/4x30-1/5	30-1/5x34-1/2x30-1/5	30-1/5x34-1/2x30-1/5
	Net/Gross weight	kg	61/65	67/71	87/92	87/92
		lbs	134/143	148/157	192/203	192/203
Refrigerant system	Liquid side/ Gas side	inch	3/8 / 3/4	3/8 / 3/4	3/8 / 7/8	3/8 / 7/8
	Factory charge R410A	oz	78	114	152	163
	Metering device		/	/	/	/
Operating temperatures		°F	40-120	40-120	40-120	40-120
Maximum line length		Feet	100	100	100	100
Maximum elevation difference		Feet	50	50	50	50
Shipping per STD40HQ			180	180	135	135