

# SUBMITTAL DATA SHEET



## Heater

Location: \_\_\_\_\_  
 Engineer: \_\_\_\_\_  
 Submitted to: \_\_\_\_\_  
 Submitted by: \_\_\_\_\_  
 Reference: \_\_\_\_\_

Approval: \_\_\_\_\_  
 Date: \_\_\_\_\_  
 Construction: \_\_\_\_\_  
 Unit #: \_\_\_\_\_  
 Drawing #: \_\_\_\_\_

<b>Model</b>	EAH-25B(UL) ComfortStar	
Normal Operational Voltage	(V, Ph, Hz)	208/230, 1, 60
Current	A	90.1/100
Heat Power	kW	18.75/23
MCA(Circuit 1)	A	23/27
MAX. FUSE(Circuit 1)	A	25/30
MCA(Circuit 2)	A	46/53
MAX. FUSE(Circuit 2)	A	50/60
MCA(Circuit 3)	A	46/53
MAX. FUSE(Circuit 3)	A	50/60
Heater dimension	mm	535x300x204
	inch	21.06x11.81x8.03
Packaging dimension	mm	610x415x260
	inch	24.02x16.34x10.24
Net Weight	kg	6
	lbs	12
Gross Weight	kg	9
	lbs	19



### Indoor unit dimension

