

COOLING PERFORMANCE DATA

Model	Cooling		Outdoor conditions (DB)																				
	DB	WB	Indoor																				
			-22°F -30°C	-13°F -25°C	-4°F -20°C	0°F -17.8°C	5°F -15°C	17°F -8.3°C	25°F -3.9°C	35°F 1.7°C	47°F 8.3°C	55°F 12.8°C	65°F 18.3°C	75°F 24°C	80°F 26.7°C	85°F 29.4°C	95°F 35°C	105°F 40.5°C	110°F 43.3°C	115°F 46°C	122°F 50°C		
CPA-09B CHF09CD(O) (208-230V)	65°F (18.3°C)	54°F(12 .2°C)	TC	7.45	8.00	8.19	8.36	8.67	8.73	8.86	9.10	9.69	10.10	10.62	10.77	11.17	10.55	10.37	9.62	9.15	8.84	7.92	
		70°F (21.1°C)	59°F (15°C)	SC	4.57	5.25	5.48	5.60	5.88	6.14	6.45	6.63	7.01	7.67	8.17	8.39	8.59	8.35	8.50	8.10	8.28	8.31	7.92
			Input	0.26	0.31	0.35	0.37	0.38	0.46	0.48	0.53	0.66	0.70	0.76	0.76	0.80	0.93	1.18	1.17	1.12	1.23	1.23	
	75°F (23.9°C)	63°F(17 .2°C)	TC	7.88	8.41	8.65	8.89	9.16	9.15	9.42	9.57	10.31	10.66	11.12	11.39	11.75	11.11	11.03	10.20	9.68	9.26	8.30	
		80°F (26.7°C)	67°F(19 .4°C)	SC	4.80	5.49	5.77	5.91	6.18	6.41	6.82	6.93	7.41	8.04	8.50	8.82	8.99	8.74	8.98	8.55	8.71	8.66	8.27
			Input	0.26	0.31	0.35	0.37	0.39	0.45	0.48	0.52	0.66	0.70	0.74	0.77	0.79	0.93	1.18	1.17	1.13	1.22	1.23	
	75°F (23.9°C)	63°F(17 .2°C)	TC	8.37	8.85	9.20	9.37	9.54	9.58	9.86	10.18	10.85	11.29	11.58	11.90	12.36	11.76	11.60	10.84	10.26	9.67	8.83	
			SC	5.08	5.74	6.10	6.19	6.40	6.68	7.11	7.33	7.77	8.47	8.81	9.16	9.40	9.21	9.39	9.03	9.19	8.98	8.77	
		Input	0.27	0.31	0.35	0.37	0.38	0.45	0.48	0.53	0.66	0.71	0.73	0.76	0.80	0.94	1.19	1.17	1.15	1.20	1.25		
CPA-12B CHF12CD(O) (208-230V)	65°F (18.3°C)	54°F(12 .2°C)	TC	8.49	9.38	9.56	9.75	10.17	10.11	10.61	11.18	11.02	11.49	11.88	12.05	12.25	12.26	12.44	11.63	11.32	10.23	9.41	
		70°F (21.1°C)	59°F (15°C)	SC	5.28	6.07	6.14	6.35	6.99	7.01	7.46	7.98	8.03	8.97	9.31	9.30	9.62	9.86	10.11	9.73	10.10	9.54	9.34
			Input	0.34	0.40	0.44	0.48	0.51	0.63	0.65	0.71	0.79	0.82	0.85	0.87	0.90	1.05	1.29	1.29	1.31	1.34	1.37	
	75°F (23.9°C)	63°F(17 .2°C)	TC	8.90	9.81	10.14	10.27	10.60	10.66	11.22	11.74	11.62	12.05	12.45	12.82	13.03	12.97	12.97	12.22	11.82	10.74	9.83	
			SC	5.50	6.31	6.48	6.64	7.24	7.35	7.85	8.35	8.42	9.36	9.71	9.85	10.17	10.37	10.48	10.17	10.48	9.96	9.73	
		Input	0.34	0.40	0.44	0.47	0.50	0.63	0.66	0.70	0.80	0.82	0.85	0.88	0.91	1.06	1.28	1.29	1.29	1.33	1.35		
	80°F (26.7°C)	67°F(19 .4°C)	TC	9.41	10.28	10.59	10.89	11.07	11.21	11.77	12.26	12.19	12.76	13.15	13.51	13.68	13.71	13.77	12.93	12.48	11.38	10.36	
			SC	5.78	6.58	6.74	7.00	7.52	7.69	8.19	8.67	8.78	9.85	10.19	10.33	10.63	10.91	11.08	10.71	11.01	10.50	10.20	
		Input	0.34	0.40	0.44	0.47	0.50	0.63	0.67	0.70	0.79	0.82	0.85	0.89	0.90	1.06	1.30	1.29	1.29	1.34	1.35		
80°F (26.7°C)	67°F(19 .4°C)	TC	9.98	10.74	11.18	11.36	11.53	11.77	12.39	13.01	12.93	13.33	13.75	14.17	14.54	14.51	14.48	13.74	13.03	12.10	10.99		
		SC	6.10	6.83	7.08	7.27	7.78	8.03	8.58	9.16	9.26	10.24	10.60	10.79	11.24	11.48	11.58	11.31	11.43	11.09	10.78		
	Input	0.35	0.40	0.44	0.47	0.49	0.63	0.66	0.70	0.79	0.82	0.85	0.88	0.91	1.23	1.31	1.29	1.28	1.34	1.37			
CPA-18B CHF18CD(O) (208-230V)	65°F (18.3°C)	54°F(12 .2°C)	TC	14.18	14.71	15.08	15.53	15.76	16.10	16.16	16.10	16.22	17.06	17.72	18.83	19.46	17.70	16.65	15.41	14.75	14.06	12.70	
		70°F (21.1°C)	59°F (15°C)	SC	8.90	9.50	9.86	10.32	10.70	11.75	11.58	11.87	12.15	13.17	14.03	14.74	15.32	13.77	13.41	13.16	13.05	13.04	12.67
			Input	0.55	0.63	0.68	0.72	0.77	0.82	0.85	0.89	0.97	1.03	1.10	1.19	1.27	1.51	1.89	1.80	1.81	1.94	2.02	
	75°F (23.9°C)	63°F(17 .2°C)	TC	14.82	15.53	16.01	16.18	16.58	17.06	17.14	16.94	17.02	17.92	18.64	19.61	20.52	18.73	17.60	16.36	15.69	14.88	13.52	
			SC	9.24	9.99	10.40	10.69	11.19	12.38	12.20	12.44	12.69	13.74	14.67	15.26	16.06	14.49	14.10	13.90	13.80	13.71	13.42	
		Input	0.55	0.63	0.69	0.72	0.76	0.83	0.87	0.89	0.96	1.03	1.10	1.17	1.26	1.51	1.91	1.83	1.84	1.97	2.02		
	80°F (26.7°C)	67°F(19 .4°C)	TC	15.44	16.20	16.91	17.15	17.41	18.01	17.93	17.93	18.03	18.86	19.72	20.58	21.67	19.88	18.37	17.33	16.55	15.51	14.09	
			SC	9.58	10.35	10.92	11.27	11.70	13.00	12.70	13.10	13.37	14.38	15.44	15.92	16.86	15.30	14.63	14.64	14.48	14.22	13.94	
		Input	0.54	0.62	0.69	0.73	0.76	0.84	0.85	0.90	0.98	1.04	1.11	1.17	1.26	1.50	1.90	1.86	1.85	1.94	2.01		
80°F (26.7°C)	67°F(19 .4°C)	TC	16.16	17.01	17.72	17.98	18.27	19.10	19.01	18.93	19.12	20.04	20.91	21.80	22.67	20.86	19.38	18.35	17.44	16.23	14.77		
		SC	9.97	10.82	11.38	11.74	12.21	13.70	13.38	13.76	14.09	15.21	16.29	16.76	17.55	15.98	15.35	15.42	15.17	14.80	14.55		
	Input	0.54	0.62	0.69	0.73	0.77	0.84	0.87	0.90	0.99	1.05	1.12	1.18	1.26	1.78	1.89	1.87	1.85	1.92	2.01			
CPA-24B CHF24CD(O) (208-230V)	65°F (18.3°C)	54°F(12 .2°C)	TC	20.86	22.10	22.68	23.00	23.29	24.58	24.96	25.94	29.24	29.45	30.11	29.72	29.65	27.00	24.13	22.79	21.22	19.62	17.72	
		70°F (21.1°C)	59°F (15°C)	SC	12.87	13.93	15.25	15.02	16.10	17.95	18.02	18.49	21.93	22.49	23.52	22.74	23.41	21.05	19.26	19.32	18.89	18.72	17.64
			Input	1.02	1.20	1.28	1.38	1.44	1.50	1.51	1.65	1.99	2.00	2.08	2.08	2.04	2.26	2.48	2.41	2.33	2.43	2.63	
	75°F (23.9°C)	63°F(17 .2°C)	TC	21.91	23.36	23.90	24.16	24.67	25.68	26.44	27.39	30.49	31.07	31.43	31.02	31.51	28.36	25.32	23.86	22.53	20.83	18.58	
			SC	13.45	14.65	15.99	15.70	16.95	18.66	18.96	19.42	22.74	23.59	24.43	23.62	24.74	22.00	20.09	20.13	19.94	19.75	18.40	
		Input	1.02	1.20	1.28	1.37	1.45	1.48	1.54	1.65	1.97	2.01	2.07	2.05	2.07	2.26	2.47	2.42	2.36	2.47	2.61		
	80°F (26.7°C)	67°F(19 .4°C)	TC	23.24	24.54	25.13	25.49	26.02	27.04	27.83	28.62	32.33	32.57	33.08	32.86	33.35	29.85	26.62	24.99	23.69	21.74	19.54	
			SC	14.18	15.29	16.72	16.46	17.78	19.53	19.85	20.16	23.96	24.60	25.56	24.89	26.01	23.02	21.01	20.95	20.85	20.53	19.27	
		Input	1.03	1.20	1.29	1.36	1.46	1.46	1.53	1.62	2.00	2.01	2.06	2.08	2.10	2.25	2.46	2.40	2.38	2.43	2.59		
80°F (26.7°C)	67°F(19 .4°C)	TC	24.33	25.61	26.68	27.09	27.51	28.64	29.48	30.26	33.82	34.17	34.50	34.85	35.18	31.46	27.88	26.36	25.09	23.13	20.63		
		SC	14.77	15.88	17.66	17.39	18.70	20.56	20.90	21.18	24.92	25.66	26.53	26.24	27.30	24.13	21.89	21.96	21.96	21.70	20.26		
	Input	1.03	1.18	1.32	1.39	1.46	1.46	1.54	1.62	1.98	2.02	2.05	2.08	2.11	2.33	2.44	2.41	2.39	2.48	2.57			
CPA-36DUB CHF36CD(O) (208-230V)	65°F (18.3°C)	54°F(12 .2°C)	TC	30.12	32.11	32.92	34.07	31.40	31.80	32.24	33.13	36.31	36.49	36.32	35.51	36.28	34.28	31.61	30.97	29.51	27.04	24.34	
		70°F (21.1°C)	59°F (15°C)	SC	18.39	19.66	20.80	21.68	22.34	22.26	22.69	23.59	26.71	28.39	27.45	27.51	28.56	27.52	25.22	26.18	26.80	25.42	24.32
			Input	1.71	1.95	2.17	2.31	2.92	3.05	3.09	3.12	3.56	3.70	3.88	3.97	4.15	4.31	4.18	4.34	4.31	4.34	4.46	
	75°F (23.9°C)	63°F(17 .2°C)	TC	31.77	33.73	34.83	35.60	33.02	33.16	33.62	34.84	38.22	38.08	38.59	37.73	38.47	35.71	33.62	32.33	30.81	28.38	25.41	
			SC	19.30	20.51	21.88	22.54	23.35	23.10	23.52	24.64	27.97	29.49	29.00	29.10	30.14	28.50	26.68	27.18	27.81	26.55	25.30	
		Input	1.69	1.95	2.16	2.28	2.89	3.00															

CPA-48DUB CHF48CD(O) (208-230V)	65°F (18.3°C)	54°F(12 .2°C)	TC	39.81	42.43	43.51	45.03	46.15	46.53	45.33	46.11	46.98	47.49	47.75	47.17	48.65	47.30	45.76	44.01	40.89	38.79	34.88
			SC	24.84	26.56	28.09	29.29	31.62	32.60	31.85	34.46	34.42	35.44	37.79	37.78	38.59	37.56	36.34	36.77	36.27	36.10	34.64
			Input	1.98	2.26	2.51	2.68	2.63	2.76	2.68	2.76	2.94	3.14	3.45	3.63	4.11	4.88	6.04	6.09	5.95	6.22	6.12
	70°F (21.1°C)	59°F (15°C)	TC	42.48	45.09	46.57	47.59	48.22	48.57	47.92	48.28	49.34	50.25	50.80	50.12	50.84	49.27	48.22	46.13	43.08	40.49	36.87
			SC	26.39	28.05	29.92	30.83	32.89	33.86	33.48	35.88	35.98	37.28	40.00	39.92	40.12	38.92	38.07	38.33	38.05	37.47	36.46
			Input	1.99	2.28	2.53	2.67	2.62	2.71	2.70	2.74	2.90	3.16	3.45	3.66	4.07	4.81	6.10	6.12	5.98	6.13	6.09
	75°F (23.9°C)	63°F(17 .2°C)	TC	43.71	44.59	47.13	49.35	50.98	51.39	50.82	50.39	52.22	52.73	53.02	53.04	53.46	51.87	50.92	48.30	45.07	42.62	38.48
			SC	28.54	29.11	30.85	33.37	34.56	35.65	35.29	37.27	37.83	38.88	41.51	42.05	41.93	40.72	39.95	39.89	39.58	39.20	37.91
			Input	1.97	2.25	2.48	2.63	2.61	2.74	2.74	2.73	2.93	3.17	3.40	3.66	4.06	4.85	6.08	6.04	5.90	6.06	6.03
	80°F (26.7°C)	67°F(19 .4°C)	TC	46.28	48.72	50.75	51.59	54.23	53.81	53.61	53.38	55.43	55.51	55.58	55.66	55.74	54.54	53.16	50.74	47.84	44.63	40.30
			SC	28.41	29.95	32.25	33.04	36.55	37.13	36.99	39.24	39.91	40.74	43.24	43.86	43.48	42.60	41.51	41.66	41.81	40.84	39.53
			Input	1.97	2.22	2.46	2.60	2.62	2.70	2.73	2.77	2.96	3.18	3.40	3.67	3.99	5.65	6.02	5.99	5.90	6.06	6.02
CPA-60DU CHF60CD(O) (208-230V)	65°F (18.3°C)	54°F(12 .2°C)	TC	49.46	52.73	54.06	55.95	59.384	58.886	59.907	60.633	57.455	55.811	57.518	54.627	53.841	52.891	51.728	42.224	34.077	26.762	19.526
			SC	30.50	32.60	34.49	35.95	39.924	42.999	42.519	43.79	41.904	43.452	43.716	43.32	41.544	42.197	42.754	34.839	30.246	24.698	19.5
			Input	2.85	3.25	3.62	3.85	4.086	4.082	4.255	4.337	4.283	4.368	4.458	4.411	4.355	5.171	6.461	5.506	4.552	3.892	3.046
	70°F (21.1°C)	59°F (15°C)	TC	52.84	56.09	57.93	59.20	62.378	62.446	62.403	63.291	60.928	59.247	59.915	57.624	56.201	56.028	53.939	44.353	35.946	27.906	20.382
			SC	32.44	34.49	36.78	37.89	41.674	45.353	44.044	45.414	44.167	45.852	45.302	45.451	43.163	44.416	44.351	36.403	31.724	25.605	20.276
			Input	2.85	3.28	3.64	3.84	4.056	4.155	4.184	4.328	4.36	4.363	4.44	4.379	4.282	5.155	6.454	5.483	4.58	3.831	2.989
	75°F (23.9°C)	63°F(17 .2°C)	TC	54.21	55.29	58.45	61.20	65.318	65.526	65.004	66.135	63.666	63.029	62.476	60.276	59.725	58.73	57.382	46.638	37.838	29.252	21.614
			SC	34.96	35.66	37.78	40.87	43.373	47.348	45.651	47.219	45.858	48.512	46.952	47.302	45.609	46.28	46.938	38.043	33.208	26.68	21.412
			Input	2.85	3.26	3.60	3.81	4.001	4.186	4.162	4.291	4.355	4.428	4.417	4.342	4.323	5.187	6.454	5.426	4.614	3.775	3.036
	80°F (26.7°C)	67°F(19 .4°C)	TC	57.87	60.92	63.46	64.51	68.683	69.12	69.079	69.034	66.946	65.999	65.08	64.123	63.268	61.821	60.402	49.041	39.746	31.02	22.969
			SC	35.15	37.07	39.91	40.89	45.399	49.628	48.286	49.014	47.933	50.555	48.679	50.016	48.084	48.406	49.167	39.772	34.698	28.135	22.67
			Input	2.83	3.18	3.54	3.73	3.993	4.182	4.22	4.265	4.388	4.382	4.375	4.37	4.374	6.196	6.448	5.426	4.571	3.843	3.065

HEATING PERFORMANCE DATA

Model	Heating		Outdoor conditions (DB)														
	Indoor Conditions DB		-22°F	-13°F	-4°F	0°F	5°F	10°F	17°F	20°F	25°F	32°F	35°F	40°F	47°F	50°F	57°F
			-30°C	-25°C	-20°C	-17.8°C	-15°C	-12.2°C	-8.3°C	-6.7°C	-3.9°C	0°C	1.7°C	4.4°C	8.3°C	10°C	13.9°C
CPA-09B CHF09CD(O) (208-230V)	60°F (15.6°C)	TC	7.56	8.61	9.65	10.07	10.42	12.08	13.45	13.78	14.16	14.63	14.81	15.10	15.55	16.04	16.49
		Input	1.73	1.70	1.63	1.59	1.55	1.72	1.82	1.86	1.89	1.93	2.00	1.64	1.42	1.37	1.36
	65°F (18.3°C)	TC	7.35	8.40	9.41	9.83	10.16	11.75	13.08	13.42	13.72	14.13	14.39	14.73	15.11	15.59	15.96
		Input	1.77	1.75	1.67	1.63	1.60	1.75	1.86	1.90	1.94	1.99	2.05	1.68	1.46	1.41	1.39
	70°F (21.1°C)	TC	7.13	8.20	9.11	9.54	9.90	11.44	12.73	13.04	13.36	13.67	14.02	14.36	14.72	15.10	15.45
		Input	1.81	1.80	1.71	1.67	1.63	1.80	1.90	1.95	2.00	2.05	2.11	1.73	1.50	1.45	1.42
75°F (23.9°C)	TC	6.81	7.85	8.78	9.16	9.46	10.97	12.19	12.55	12.84	13.19	13.39	13.81	14.05	14.50	14.88	
	Input	1.86	1.86	1.76	1.72	1.68	1.85	1.95	2.01	2.07	2.11	2.16	1.77	1.55	1.49	1.46	
CPA-12B CHF12CD(O) (208-230V)	60°F (15.6°C)	TC	9.62	10.95	12.11	12.79	13.26	13.88	14.56	15.03	15.48	15.80	16.34	16.85	17.37	17.71	18.18
		Input	2.00	2.03	1.93	1.91	1.87	1.87	1.85	1.83	1.79	1.76	1.73	1.55	1.39	1.36	1.33
	65°F (18.3°C)	TC	9.29	10.63	11.77	12.38	12.88	13.55	14.05	14.53	14.97	15.40	15.94	16.31	16.83	17.23	17.62
		Input	2.06	2.09	1.99	1.96	1.91	1.91	1.91	1.88	1.84	1.80	1.78	1.58	1.42	1.40	1.36
	70°F (21.1°C)	TC	8.99	10.33	11.48	11.98	12.48	13.10	13.75	14.15	14.58	15.00	15.42	15.85	16.34	16.75	17.15
		Input	2.11	2.15	2.05	2.00	1.95	1.96	1.96	1.93	1.89	1.86	1.83	1.63	1.47	1.43	1.39
75°F (23.9°C)	TC	8.65	9.87	11.02	11.44	12.00	12.54	13.13	13.57	13.92	14.38	14.78	15.15	15.76	16.11	16.48	
	Input	2.17	2.21	2.11	2.06	2.01	2.02	2.02	1.99	1.95	1.91	1.88	1.67	1.50	1.46	1.43	
CPA-18B CHF18CD(O) (208-230V)	60°F (15.6°C)	TC	13.82	16.06	17.78	18.69	19.32	21.42	23.32	23.96	24.12	24.52	24.74	24.70	24.45	24.98	25.62
		Input	2.94	3.00	2.87	2.75	2.70	2.89	2.99	2.92	2.83	2.73	2.68	2.36	2.07	2.00	1.96
	65°F (18.3°C)	TC	13.44	15.64	17.26	18.08	18.81	20.76	22.73	23.20	23.51	23.78	24.12	24.01	23.83	24.35	24.90
		Input	3.01	3.06	2.92	2.83	2.76	2.95	3.08	3.00	2.89	2.79	2.74	2.43	2.13	2.05	2.01
	70°F (21.1°C)	TC	12.99	15.11	16.79	17.48	18.25	20.15	22.09	22.46	22.80	23.16	23.51	23.33	23.11	23.66	24.27
		Input	3.07	3.14	2.99	2.89	2.84	3.02	3.17	3.06	2.96	2.88	2.80	2.48	2.17	2.10	2.06
75°F (23.9°C)	TC	12.50	14.43	16.15	16.87	17.43	19.45	21.30	21.45	21.96	22.30	22.52	22.49	22.10	22.76	23.22	
	Input	3.17	3.23	3.09	2.98	2.94	3.11	3.28	3.16	3.07	2.95	2.89	2.54	2.24	2.17	2.13	
CPA-24B CHF24CD(O) (208-230V)	60°F (15.6°C)	TC	19.05	22.00	24.33	25.50	26.73	27.80	28.57	30.46	32.31	33.65	34.97	34.93	34.28	35.18	35.75
		Input	3.76	3.77	3.55	3.48	3.38	3.25	3.13	3.17	3.19	3.26	3.30	2.80	2.37	2.32	2.27
	65°F (18.3°C)	TC	18.48	21.47	23.74	24.76	26.00	27.01	27.88	29.46	31.31	32.83	34.11	33.75	33.41	33.99	34.84
		Input	3.84	3.85	3.64	3.56	3.48	3.34	3.22	3.25	3.29	3.36	3.37	2.89	2.43	2.37	2.32
	70°F (21.1°C)	TC	17.89	20.80	23.11	24.13	25.12	26.13	27.09	28.72	30.25	31.75	33.28	32.83	32.28	33.10	33.89
		Input	3.94	3.93	3.74	3.67	3.56	3.44	3.29	3.35	3.39	3.43	3.47	2.95	2.51	2.44	2.38
75°F (23.9°C)	TC	17.08	19.95	22.30	23.28	24.17	25.13	25.95	27.57	29.19	30.61	31.88	31.58	30.89	31.68	32.37	
	Input	4.04	4.04	3.86	3.76	3.65	3.53	3.38	3.46	3.48	3.55	3.56	3.04	2.59	2.52	2.46	
CPA-36DUB CHF36CD(O) (208-230V)	60°F (15.6°C)	TC	28.43	33.05	36.87	38.24	39.65	45.53	51.18	51.48	52.37	53.60	53.94	54.88	55.96	56.57	58.08
		Input	5.76	5.78	5.50	5.36	5.26	5.61	5.95	5.87	5.84	5.71	5.66	5.03	4.53	4.38	4.29
	65°F (18.3°C)	TC	27.55	31.94	35.73	36.98	38.65	44.33	49.50	49.98	50.85	51.89	52.63	53.23	54.12	55.03	56.61
		Input	5.89	5.93	5.62	5.50	5.39	5.78	6.13	6.04	5.96	5.86	5.80	5.15	4.65	4.49	4.42
	70°F (21.1°C)	TC	26.77	31.13	34.59	35.94	37.59	42.83	47.87	48.76	49.61	50.48	51.34	51.88	52.39	53.58	55.01
		Input	6.01	6.06	5.78	5.64	5.50	5.90	6.27	6.18	6.10	6.00	5.93	5.30	4.76	4.62	4.52
75°F (23.9°C)	TC	25.70	29.98	33.38	34.32	36.01	41.04	46.00	46.86	47.47	48.41	49.14	49.65	50.30	51.33	52.81	
	Input	6.20	6.26	5.97	5.82	5.69	6.07	6.43	6.39	6.31	6.21	6.10	5.44	4.92	4.74	4.65	
CPA-48DUB CHF48CD(O) (208-230V)	60°F (15.6°C)	TC	37.12	43.38	48.34	49.91	52.34	54.86	57.99	58.22	58.90	59.18	60.16	64.21	67.95	69.43	70.73
		Input	6.73	6.96	6.54	6.46	6.34	6.36	6.42	6.05	5.79	5.49	5.30	5.29	5.28	5.17	5.04
	65°F (18.3°C)	TC	36.01	42.19	46.84	48.55	50.76	53.21	56.13	56.58	57.24	57.46	58.18	62.22	65.65	67.47	68.93
		Input	6.94	7.11	6.73	6.60	6.46	6.52	6.56	6.22	5.91	5.66	5.45	5.40	5.42	5.30	5.17
	70°F (21.1°C)	TC	35.09	40.81	45.34	47.13	49.28	51.76	54.45	54.93	55.41	55.89	56.43	60.24	63.68	65.32	66.86
		Input	7.15	7.29	6.94	6.76	6.61	6.66	6.73	6.39	6.06	5.80	5.56	5.56	5.56	5.42	5.28
75°F (23.9°C)	TC	33.58	39.05	43.48	45.25	47.56	49.69	52.43	52.79	53.03	53.60	54.29	58.01	61.45	62.64	64.25	
	Input	7.40	7.54	7.13	6.97	6.84	6.82	6.90	6.59	6.25	6.00	5.71	5.75	5.72	5.58	5.44	
CPA-60DU CHF60CD(O) (208-230V)	60°F (15.6°C)	TC	29.53	37.667	46.632	50.685	56.137	57.112	57.112	57.081	57.429	58.131	58.582	63.568	69.534	71.186	73.436
		Input	5.981	6.142	6.332	6.614	6.894	6.791	6.699	6.323	6.096	5.857	5.739	5.311	4.955	4.858	4.726
	65°F (18.3°C)	TC	28.64	36.605	45.23	49.449	54.661	55.395	55.557	55.635	55.811	56.492	56.765	61.717	67.706	69.382	71.645
		Input	6.134	6.293	6.481	6.784	7.108	6.965	6.836	6.512	6.239	6.038	5.856	5.42	5.092	4.962	4.872
	70°F (21.1°C)	TC	27.73	35.505	44.127	48.242	53.172	53.573	53.991	54.225	54.449	54.688	54.899	59.861	65.926	67.69	69.222
		Input	6.266	6.475	6.668	6.986	7.328	7.151	7.012	6.713	6.432	6.18	5.982	5.542	5.234	5.1	4.972
75°F (23.9°C)	TC	26.59	33.943	42.274	46.457	51.152	51.538	51.777	52.056	52.435	52.664	52.648	57.227	62.959	65.321	66.454	
	Input	6.485	6.682	6.854	7.203	7.533	7.366	7.208	6.888	6.645	6.396	6.137	5.713	5.385	5.258	5.101	