

Project Name:	
Location:	
Engineer:	
Submitted to:	
Submitted by:	
Reference:	
Approval:	
Date:	
Construction:	
Unit #:	
Drawing #:	
Indoor unit model	CHF09CD(I)



Power supply		V- Ph-Hz	208/230, 1, 60
Cooling	Capacity (range)	Btu/hr	9000(2500~11900)
Heating	Capacity (range)	Btu/hr	10000(3400~13000)
MINIMUM CIRCUIT AMPACITY		A	3
MAX.FUSE		A	15
Indoor air flow (Hi/Mi/Lo)		CFM	335.29/229.41/176.47
Indoor noise level (Hi/Mi/Lo)		dB(A)	38/34/23
Indoor unit	Dimension(W*D*H)(body)	mm	848x230x297
		inch	33.39x9.06x11.69
	Packing (W*D*H)(body)	mm	920x370x313
		inch	36.22x14.57x12.32
	Net/Gross weight (body)	kg	11.5/13.9
		lb	25.35/30.64
Refrigerant piping	Liquid side/ Gas side	mm	6.35/9.52
		inch	1/4" / 3/8"
Thermostat type			Wireless remote controller
Temperature	Cooling	°C	16~32
		°F	60~90
	Heating	°C	0~30
		°F	32~86
Connection wiring			16AWG*4 Stranded, unshielded

Unit dimension

