

Project Name:	
Location:	
Engineer:	
Submitted to:	
Submitted by:	
Reference:	
Approval:	
Date:	
Construction:	
Unit #:	
Drawing #:	
Indoor unit model	CHF24CD(I)



Power supply		V- Ph-Hz	208/230, 1, 60
Cooling	Capacity (range)	Btu/hr	24000(9200~26800)
Heating	Capacity (range)	Btu/hr	25000(10350~27000)
MINIMUM CIRCUIT AMPACITY		A	3
MAX.FUSE		A	15
Indoor air flow (Hi/Mi/Lo)		CFM	611.18/414.12/318.82
Indoor noise level (Hi/Mi/Lo)		dB(A)	44/39.5/34
Indoor unit	Dimension(W*D*H)(body)	mm	1190x278.5x370
		inch	46.85x10.96x14.57
	Packing (W*D*H)(body)	mm	1280x455x360
		inch	50.39x17.91x14.17
	Net/Gross weight (body)	kg	22.0/26.9
		lb	48.50/59.30
Refrigerant piping	Liquid side/ Gas side	mm	9.52/15.9
		inch	3/8" / 5/8"
Thermostat type			Wireless remote controller
Temperature	Cooling	°C	16~32
		°F	60~90
	Heating	°C	0~30
		°F	32~86
Connection wiring			16AWG*4 Stranded, unshielded

Unit dimension

