

Project Name:	
Location:	
Engineer:	
Submitted to:	
Submitted by:	
Reference:	
Approval:	
Date:	
Construction:	
Unit #:	
Drawing #:	
Indoor unit model	TPA-09



Power supply		V- Ph-Hz	208/230, 1, 60
Cooling	Capacity (range)	Btu/hr	9000(2970~10500)
Heating	Capacity (range)	Btu/hr	10000(2230~11650)
MINIMUM CIRCUIT AMPACITY		A	3
MAX.FUSE		A	15
Indoor air flow (Hi/Mi/Lo)		CFM	352.94/305.88/270.59
Indoor noise level (Hi/Mi/Lo)		dB(A)	39.5/36/32.5
Indoor unit	Dimension(W*D*H)(body)	mm	570x570x260
		inch	22.44x22.44x10.24
	Packing (W*D*H)(body)	mm	662x662x317
		inch	26.06x26.06x12.48
	Net/Gross weight (body)	kg	14.5/17.3
		lb	31.97/38.14
Refrigerant piping	Liquid side/ Gas side	mm	6.35/9.52
		inch	1/4" / 3/8"
Thermostat type			Wireless remote controller
Temperature	Cooling	℃	16~32
		℉	60~90
	Heating	℃	0~30
		℉	32~86
Connection wiring			16AWG*4 Stranded, unshielded

Unit dimension

