

Project Name:	
Location:	
Engineer:	
Submitted to:	
Submitted by:	
Reference:	
Approval:	
Date:	
Construction:	
Unit #:	
Drawing #:	
Indoor unit model	TPA-12



Power supply		V- Ph-Hz	208/230, 1, 60
Cooling	Capacity (range)	Btu/hr	12000(2800~14100)
Heating	Capacity (range)	Btu/hr	12000(1950~14600)
MINIMUM CIRCUIT AMPACITY		A	3
MAX.FUSE		A	15
Indoor air flow (Hi/Mi/Lo)		CFM	379/309/261
Indoor noise level (Hi/Mi/Lo)		dB(A)	40.5/35.5/31.5
Indoor unit	Dimension(W*D*H)(body)	mm	570x570x260
		inch	22.44x22.44x10.24
	Packing (W*D*H)(body)	mm	662x662x317
		inch	26.06x26.06x12.48
	Net/Gross weight (body)	kg	16/18.6
		lb	35.27/41.01
Refrigerant piping	Liquid side/ Gas side	mm	6.35/12.7
		inch	1/4" / 1/2"
Thermostat type			Wireless remote controller
Temperature	Cooling	°C	16~32
		°F	60~90
	Heating	°C	0~30
		°F	32~86
Connection wiring			16AWG*4 Stranded, unshielded

Unit dimension

