

Project Name:	
Location:	
Engineer:	
Submitted to:	
Submitted by:	
Reference:	
Approval:	
Date:	
Construction:	
Unit #:	
Drawing #:	
Indoor unit model	TPA-18



<b>Power supply</b>		V- Ph-Hz	208/230, 1, 60
<b>Cooling</b>	Capacity (range)	Btu/hr	16000(5600~16000)
<b>Heating</b>	Capacity (range)	Btu/hr	18500(7700~18500)
<b>MINIMUM CIRCUIT AMPACITY</b>		A	1.9
<b>MAX.FUSE</b>		A	15
<b>Indoor air flow (Hi/Mi/Lo)</b>		CFM	562.35/485.29/438.82
<b>Indoor noise level (Hi/Mi/Lo)</b>		dB(A)	43.5/38.5/35.5
<b>Indoor unit</b>	Dimension(W*D*H)(body)	mm	570x570x260
		inch	22.44x22.44x10.24
	Packing (W*D*H)(body)	mm	662x662x317
		inch	26.06x26.06x12.48
	Net/Gross weight (body)	kg	16.2/21.3
		lb	35.71/46.96
<b>Refrigerant piping</b>	Liquid side/ Gas side	mm	6.35/12.7
		inch	1/4" / 1/2"
<b>Thermostat type</b>			Wireless remote controller
<b>Temperature</b>	Cooling	°C	16~32
		°F	60~90
	Heating	°C	0~30
		°F	32~86
<b>Connection wiring</b>			16AWG*4 Stranded, unshielded

# Unit dimension

