# **ComfortStar®**

## **Submittal**

#### **Split System Cooling**

#### 96M100C5B

Location:	Approval:	
Engineer:	Date:	
Submitted to:	Construction:	
Submitted by:	Unit #:	
Reference:	Drawing #:	



Note: "Graphics in this document are for representation only. Actual model may differ in appearance."

# **ComfortStar®**

#### **Unit dimension**




Fig. 1 - Dimensional Drawing

Table 1 - Dimensions

FURNACE SIZE	A CABINET WIDTH IN. (MM)	D SUPPLY- AIR WIDTH IN. (MM)	E RETURN- AIR WIDTH IN. (MM)	NET/SHIP WT (lbs)
60B3B	17.5 (445)	16 (406)	15-27/32 (402) 135/147.5	
80B3B	17.5 (445)	16 (406)	15-27/32 (402)	141/153
80C4B	21 (533)	19.5 (495)	19-13/32 (493)	152/165
100C5B	21 (533)	19.5 (495)	19-13/32 (493)	162/173
100D5B	24.5 (622)	23 (584)	22-27/32 (580)	170/185
120D5B	24.5 (622)	23 (584)	22-27/32 (580) 176/190	

96M100C5B 2



### **Specification**

Model			96M100C5B
Fuel Type		<b> -</b>	Natural Gas/Propane Gas
AFUE		%	96
Input	NG/LP(HIGH)	Btu/h	10000
	NG/LP(LOW)	Btu/h	6500
	NG/LP(HIGH)	Btu/h	95000
Output	, ,		27835
·	NG/LP(LOW)	Btu/h	62000
Air Temperature Rise		°F	35-65
Design Max. Outlet Air Temperatur	°F	165	
Certified EXT static pressure	Heating	in. WC	0.2
	Cooling	in. WC	0.5
Circulating Blower	Material	_	Metal
	Type	1_	x13 ECM
	Diameter blower wheel	Inch	12.8
	Height blower wheel	Inch	11.22
Tono AC @ 0.5" ESD	Theight blower wheel	tons	3.5/4/4.5/5
Tons AC @ 0.5" ESP		HP	1
Circuating Fan Motor	Motor Horsepower	CFM	2031
Air Flow (0.5 ESP in. WC)	High		1836
Air Flow (0.5 ESP in. WC)	Mid-High	CFM	1573
Air Flow (0.5 ESP in. WC)	Mid	CFM	1241
Air Flow (0.5 ESP in. WC)	Mid-Low	CFM	
Air Flow (0.5 ESP in. WC)	Low	CFM	820
Motor Speeds		# speeds	1050 (**** 1)
		r/min	1050 (rated)
Power Input	(High)	W	63±10%
Power Input	(Low)	W	42±10%
Max. Inlet Gas Press	Natural Gas	in. WC	10.5
	Propane Gas (LP)	in. WC	13
Min. Inlet Gas Press	Natural Gas	in. WC	4.5
	Propane Gas (LP)	in. WC	11
Flue Vent Diameter		Inch	2"/3"
Power supply		V/Hz/PH	115V/60HZ/1PH
Max Overcurrent Protection (MOP)		Amps	20
MAS.Unit Amps		Amps	11.5
Packing Dimension (without pallet)		Inch	(23-1/2)*(31)*(35-1/2)
Packing Dimension (with pallet) Net Weight (unit only)		Inch	(23.5)*(31)*(40) 162
Gross Weight		lbs	194.6

3 96M100C5B

# **ComfortStar®**

12201 N W 107th Avenue Miami, FL 33178 1.866.524.9898 Toll Free 305.500.9898 Office 305.500.9896 Fax http://www.comfortstarusa.com





The AHRI mark indicates Comfortstar participating in the AHRI Certification program. Visit ahridirectory.org for verification of individual certified products. Comfortstar reserves the right to change design and specs without notice. Comfortstar has a policy of update the data continuously.We are committed to using environmentally conscious print practices.

96M100C5B 23 Oct. 2023 Supersedes 96M100C5B (Oct.2023)