ComfortStar®

Submittal

Split System Cooling

CPH30CD(O)

Location:	
Engineer:	
Submitted to:	
Submitted by:	
Reference:	

Approval:	
Date:	
Construction:	
Unit #:	
Drawing #:	




Note: "Graphics in this document are for representation only. Actual model may differ in appearance."



ComfortStar®

Unit dimension



CPH30CD(0) 2



Specification

Outdoor unit model			CPH30CD(O)	
D	Rated	V, Ph, Hz	208/230, 1, 60	
Power supply	Voltage range	V	187-253	
MINIMUM CIRCUIT AMPACITY		Α	23	
MAX.FUSE		Α	35	
	Model		KTF310D43UMT	
	Туре		ROTARY	
	Brand		GMCC	
Compressor	Capacity	Btu/h	32380	
	Input power	W	2600	
	Refrigerant oil	ml	VG74/1000	
	Model		ZKFN-120-8-2	
	Qty.		1	
Outdoor fan motor	Input power	W	150.0	
	Output power	W	120	
	Speed	r/min	950/900/500	
Outdoor air flow (Max.)		m3/h	5100	
Outdoor air flow (Max.)		CFM	3000.00	
Outdoor noise level (So	ound pressure)	dB(A)	61.5	
Throttle type			EEV for Heating	
	Dimension(W×D×H)	mm	946x410x810	
	Diffiension(vv ^D^H)	inch	37.24x16.14x31.89	
Outdoor unit	Dooking (MyDyU)	mm	1090x500x885	
Outdoor unit	Packing (W×D×H)	inch	42.91x19.69x34.84	
	Not/Cross weight	kg	72.5/77	
	Net/Gross weight	lbs.	159.83/169.75	
Refrigerant	Type/Charged	g	R410A/3800	
Keingerant	r ype/Charged	oz	R410A/134.04	
Additional charge		g/m	65	
Additional charge		oz/ft	0.69	
Design pressure		PSIG	550/340	
	Liquid side/Gas side	mm	9.52/19	
	Liquid side/Gas side	inch	3/8" / 3/4"	
Definerent nining	Max. pipe length	m	65	
Refrigerant piping	Max. pipe length	ft	213	
	Max. difference in level	m	30	
	IVIAX. UITIETETICE III IEVEI	ft	98	
	Cooling	${\mathbb C}$	-30~50	
Ambient temperature	Cooling	°F	-22 ∼122	
Ambient temperature	Heating	\mathbb{C}	-30∼24	
	ricating	°F	-22 ∼75	

Outdoor Unit	Indoor Unit	Cooling Capacity	EER2	SEER2	HSPF	HSPF2
CPH30CD(O)	AHU30-SG2	30000(10400~33600)	10	16.2	10.5	8.9
CPH30CD(O)	ACP-36C	30000(9900~35000)	10.5	15.5	9.7	7.7

3 CPH30CD(O)



12201 N W 107th Avenue Miami, FL 33178 1.866.524.9898 Toll Free 305.500.9898 Office 305.500.9896 Fax http://www.comfortstarusa.com





The AHRI mark indicates Comfortstar participating in the AHRI Certification program. Visit ahridirectory.org for verification of individual certified products. Comfortstar reserves the right to change design and specs without notice. Comfortstar has a policy of update the data continuously.We are committed to using environmentally conscious print practices.

CPH30CD(O) 8th DEC. 2023 Supersedes CPH30CD(O) (DEC.2023)