ComfortStar®

Submittal

Split System Cooling

BAR4-30-15

Location:
Engineer:
Submitted to:
Submitted by:
Reference:


Approval:
Date:
Construction:
Unit #:
Drawing #:



Note: "Graphics in this document are for representation only. Actual model may differ in appearance."

ComfortStar®

Unit dimension



UNIT DIMENSION	18K	24K	30K	36K	42K	48K	60K
Height (in.)	25	25	25	25	32-7/8	32-7/8	32-7/8
Width (in.)	21-4/5	21-4/5	29-1/7	29-1/7	29-1/7	29-1/7	29-1/7
Depth (in.)	21-4/5	21-4/5	29-1/7	29-1/7	29-1/7	29-1/7	29-1/7

BAR4-30-15 2



Specification

Model			BAR4-30-15
Outdoor power supply		V/Ph/Hz	230V/1N/60HZ
Max. input consumption		W	2991
Max. current		А	13.69
Compressor	Brand		LG
	Model		APG024KAC
	Туре		scroll
	Capacity	Btu/h	32700
	Input	W	1521
	TYPE		ECM
	Model		DRN-310-200-10
	Output	W	200
Outdoor fan motor	Horspower	HP	3/11
	rate current	А	1.3
	FLA	А	0.65
	Speed	rpm	950
Outdoor air flow		CFM	1900
Outdoor noise level		dB(A)	61.5
Throttling type			Piston
	Unit (WxHxD)	in	29-1/7×25×29-1/7
Outdoor dimension		mm	740×633×740
Outdoor diffierision	Packing (WxHxD)	in	29-9/10×25-9/10×29-9/10
		mm	760×660×760
Refrigerant	Туре		R410A
Reingerant	Charging	oz	111.11
Refrigerant pipe	Liquid side	in	Ф3/8
	Gas side	in	Ф3/4
Design pressure		MPa	4.0/1.2
Max pressure		MPa	4.2
Operation temp range	Cooling	F	58-115
Operation temp range	Heating	°F	19-75

Outdoor Uni	t Indoor Uni	it Cooling Capa	city EER2	SEER2
BAR4-30-15	LUC4-30-1	5 28000	11.7	14.3
BAR4-30-15	CWM4-30-3	15 28000	11.7	14.3

3 BAR4-30-15



12201 N W 107th Avenue Miami, FL 33178 1.866.524.9898 Toll Free 305.500.9898 Office 305.500.9896 Fax http://www.comfortstarusa.com





The AHRI mark indicates Comfortstar participating in the AHRI Certification program. Visit ahridirectory.org for verification of individual certified products. Comfortstar reserves the right to change design and specs without notice. Comfortstar has a policy of update the data continuously.We are committed to using environmentally conscious print practices.

BAR4-30-15 16th Jan 2024 Supersedes BAR4-30-15 (Jan 2024)