

ComfortStar®

Air Conditioning & Heating Products

CH32
eco
smart series™ **Wi-Fi**



17 SEER2



HIGH EFFICIENCY - HEAT PUMP DUCTLESS MINI-SPLIT SYSTEMS



Wi-Fi



Refrigerant
Leak Detector



Turbo Mode



Intelligent
Defrost



Quiet
Operation



ECO
Friendly

FEATURES:

- Dehumidifier
- 24H Timer
- Turbo Mode
- Auto Mode
- Smart Sleep
- ECO Friendly
- Display On/off
- Emergency Button
- Intelligent Defrost
- Anti-cold Wind
- Louver Position Memory
- High Efficiency Filter
- Error Code Display

Comfort, it's in our name.



© 12860 N.W. South River Dr. | Medley, FL 33178

☎ **Toll Free:** 1-866-524-9898 | **Phone:** 1-305-500-9898 | **Fax:** 1-305-500-9896 **Email us:** info@comfortstarusa.com ✉

www.comfortstarusa.com 🌐

CH32 Series eco smart series™



Indoor Unit			CH32-12CA(I)	CH32-12CD(I)	CH32-18CD(I)	CH32-24CD(I)	
Outdoor Unit			CH32-12CA(O)	CH32-12CD(O)	CH32-18CD(O)	CH32-24CD(O)	
Power Supply			1Ph / 115V/60Hz	1Ph / 208-230V/60Hz	1Ph / 208-230V/60Hz	1Ph / 208-230V/60Hz	
Power Supply	Rated Cooling Capacity	Btu/h	12000(2700~13000)	12000(2700~13000)	18000(2700~19000)	24000(2700~25000)	
		W	3500	3500	5100	7000	
	Rated Current	A	10.7(1.3~13.9)	5.66(0.7~7.7)	8.43(0.7~11.6)	11.2(1.4~14.35)	
	Rated Input	W	1230(150~1600)	1230(150~1650)	1800(150~2500)	2400(300~3000)	
	EER	Btu/W.h	9.70	9.70	9.70	9.80	
SEER2	Btu/W.h	17.0	17.0	17.0	17.0		
Heating	Rated Cooling Capacity	Btu/h	12000(2700~13000)	12000(2700~13000)	18000(2700~19000)	24000(2700~25000)	
		W	3500	3500	5100	7000	
	Rated Current	A	10.3(1.3~13.9)	4.97(0.7~7.7)	8.43(0.7~11.6)	11.7(1.4~14.35)	
	Rated Input	W	1180(150~1600)	1180(150~1650)	1750 (150~2500)	2350(300~3000)	
	HSPF2	Btu/W.h	8.0	8.0	8.0	8.0	
COP	W/W	2.96	2.96	2.92	2.97		
Max. Input Consumption		W	1600	1650	2500	3000	
Max Current		A	13.9	7.7	11.6	14.35	
Moisture Removal		Pint/h	1.7	1.7	5.5	5.3	
Indoor Air Flow (Hi/Mi/Lo)		CFM	353/294/247	353/294/247	618/559/471	736/677/589	
Indoor Noise Level (Hi/Mi/Lo)		dB(A)	42/40/38	42/40/38	49/47/45	51/48/46	
Indoor Unit	Net Dimensions		In.	30.12x12.01x7.87	30.12x12.01x7.87	38.19x12.2x9.06	40.55x13.15x9.13
	Net Weight		Lbs.	19.18	19.62	26.01	31.52
	Packing Dimensions		In.	32.28x14.17x10.63	32.28x14.17x10.63	40.75x14.96x12.2	43.5x16.14x12.6
	Gross Weight		Lbs.	22.26	22.48	30.20	35.93
Outdoor Noise Level		dB(A)	52	52	55	57	
Outdoor Unit	Net Dimensions		In.	27.56x11.89x20.08	27.56x11.89x20.08	31.5x11.89x21.65	33.86x14.88x23.5
	Net Weight		Lbs.	49.38	49.38	62.83	74.51
	Packing Dimensions		In.	30.12x13.58x21.65	30.12x13.58x21.65	34.25x13.98x23.43	37.2x16.93x26.38
	Gross Weight		Lbs.	53.57	53.57	67.24	78.92
Refrigerant		oz	R32/19.93	R32/19.22	R32/34.74	R32/40.92	
Design Pressure		PSI	798	798	798	798	
Connecting Pipe	Gas		In.	3/8"	3/8"	1/2"	1/2"
	Liquid		In.	1/4"	1/4"	1/4"	1/4"
	Max. Refrigerant Pipe Length		ft.	33	33	33	49
	Max. Difference in Level		ft.	16	16	16	33
Operation Temperature Range		°F	19~109	19~109	19~109	19~109	
Ambient Temperature Range		°F	19~118	19~118	19~118	19~118	
Application Area		sq.ft	108~215	108~215	215~430	323~592	

ComfortStar®
Air Conditioning & Heating Products



© 12860 N.W. South River Dr. | Medley, FL 33178

Toll Free: 1-866-524-9898 | Phone: 1-305-500-9898 | Fax: 1-305-500-9896 Email us: info@comfortstarusa.com

CH32-KRI2025