

ComfortStar®

Air Conditioning & Heating Products



CH32
eco
smart series™



17 SEER2



HIGH EFFICIENCY - HEAT PUMP DUCTLESS MINI-SPLIT SYSTEMS



Refrigerant
Leak Detector



Turbo Mode



Intelligent
Defrost



Quiet
Operation



ECO
Friendly

FEATURES:

- Dehumidifier
- 24H Timer
- Turbo Mode
- Auto Mode
- Smart Sleep
- ECO Friendly
- Display On/off
- 4-way Air Flow
- Emergency Button
- Intelligent Defrost
- Anti-cold Wind
- Self-troubleshooting
- Louver Position Memory
- High Efficiency Filter
- Follow Me/ I FEEL
- Error Code Display

Comfort, it's in our name.



© 12860 N.W. South River Dr. | Medley, FL 33178

Toll Free: 1-866-524-9898 | Phone: 1-305-500-9898 | Fax: 1-305-500-9896 Email us: info@comfortstarusa.com

www.comfortstarusa.com

CH32 Series



Indoor Unit			CH32-12CA(I)	CH32-12CD(I)	CH32-18CD(I)	CH32-24CD(I)	CH32-36CD(I)
Outdoor Unit			CH32-12CA(O)	CH32-12CD(O)	CH32-18CD(O)	CH32-24CD(O)	CH32-36CD(O)
Power Supply			115V~/60Hz/1P	208/230V~/60Hz/1P	220-240V~/60Hz/1P	208-230V~/60Hz/1P	208-230V~/60Hz/1P
Cooling	Rated Cooling Capacity (95F/35C)	Btu/h	12000	12000	18000	24000	36000
	Rated Current	A	10.38	5.1	8	10.3	15.2
	Rated Input	W	1180	1170	1770	2350	3430
	EER2 (95F/35C)	Btu/W.h	9.4	9.5	9	9.5	10
	SEER2	Btu/W.h	17	17	17	17	17
Heating	Rated Heating Capacity (47F/8.3C)	Btu/h	11500	12000	16500	22000	36000
	Rated Current	A	8.78	4.8	6.5	8.5	13.9
	Rated Input	W	1005	1100	1440	1900	3150
	HSPF2 Rating (Region IV)	Btu/W.h	9.5	8.3	8.5	9.5	8.5
	HSPF2 Rating (Region V)	Btu/W.h	8.1	7.1	7.2	8.5	7.5
	COP2 (47F/8.3C)	W/W	3.3	3.2	3.2	3.3	3.2
	Max. Heating Capacity (5°F/-15°C)	W/W	8100	8700	10000	12000	21500
	COP2 (5°F/-15°C)	W/W	1.9	1.8	2	2	2
Max Current	A	2.0~14.0	8	12	13	21	
Current Range	A	2.0~13.0	2~8	1.4~12.0	1.5~12.0	2.7~18.5	
Moisture Removal	Pint/h	2.75	2.75	3.38	5.07	6.34	
Indoor Air Circulation-Turbo/Hi/Mid/Lo/Mute	CFM	277/265/241/224/206	294/265/235/206/159	589	589	883/742/565/459/412	
Indoor Noise Level at Cooling	Turbo/High/Med./Low/Mute	dB(A)	42.9/40/36.1/33/29	45/42/39/35/33	49/45/43/40/37/34/32	50/48/47/46/43/40/37	55/52/46/41/39
Indoor Unit	Net Dimensions (W x D x H)	In.	30.59x9.84x7.91	30.59x9.84x7.91	35.82x11.57x8.11	39.76x12.40x8.66	46.93x14.17x10.23
	Net Weight	Lbs.	16.53	16.53	20.94	26.46	38.58
	Packing Dimensions (W x D x H)	In.	33.07x12.40x10.23	33.07x12.40x10.23	38.54x14.64x10.90	43.14x15.35x11.69	49.60x16.92x12.91
	Gross Weight (without pipe)	Lbs.	20.94	20.94	27.56	33.07	46.30
Outdoor Noise Level		dB(A)	53	55	57	56	63
Outdoor Unit	Net Dimensions (W x D x H)	In.	30.98x11.41x19.60	30.98x11.41x19.60	31.88x12.00x21.61	33.97x13.74x23.70	38.50x16.57x31.61
	Net Weight (without pipe)	Lbs.	46.30	45.19	52.91	65.04	105.82
	Packing Dimensions (W x D x H) (without pipe)	In.	32.20x12.79x20.27	32.20x12.79x20.27	33.54x14.09x23.62	35.03x15.15x24.72	40.23x18.89x31.92
	Packing Dimensions (W x D x H) (with pipe)	In.	32.99x13.30x21.25	32.99x13.30x21.25	33.54x14.09x24.02	35.43x15.94x25.39	40.23x18.89x32.87
	Gross Weight without Pipe	Lbs.	50.71	49.60	58.42	70.55	114.64
	Gross Weight with 5m Pipe	Lbs.	52.91	51.81	60.63	73.85	120.15
Connecting Pipe	Gas	In.	3/8"	3/8"	3/8"	1/2"	5/8"
	Liquid	In.	1/4"	1/4"	1/4"	1/4"	1/4"
Connecting Wiring	Size x Core Number		4x16AWG	4x16AWG	4x16AWG	4x0.75mm2	4x16AWG
Refrigerant	g		R32/500	R32/500	R32/670	R32/1040	R32/1590
	oz		R32/17.60	R32/17.60	R32/23.60	R32/36.70	R32/56.10
Additional Refrigerant Charge	oz/ft		0.11	0.11	0.11	0.11	0.11
Control Type			Remote	Remote	Remote	Remote	Remote
Suitable Area	sq.ft		Up to 550	Up to 550	Up to 1000	Up to 1500	Up to 2500
Ambient Temperature	Indoor (Cooling/ Heating)	°F	>=62/<=86	>=62/<=86	>=62/<=86	>=62/<=86	>=62/<=86
	Outdoor (Cooling/ Heating)	°F	53.6~122/5~86	53.6~122/5~86	53.6~122/5~86	53.6~122/5~86	53.6~122/5~86



© 12860 N.W. South River Dr. | Medley, FL 33178

www.comfortstarusa.com

Toll Free: 1-866-524-9898 | Phone: 1-305-500-9898 | Fax: 1-305-500-9896 | Email us: info@comfortstarusa.com

CH32-KAI2024