



Submittal

Heat pump System

BAH5-24-15

Location: _____
Engineer: _____
Submitted to: _____
Submitted by: _____
Reference: _____


Approval: _____
Date: _____
Construction: _____
Unit # : _____
Drawing # : _____



Note:" Graphics in this document are for representation only.Actual model may differ in appearance."



Unit dimension



Unit Dimensions			
Model	H(inches)	W(inches)	L(inches)
18	24-15/16	23-5/8	23-5/8
24/30	24-15/16	28	28
36	33-3/16	28	28
42/48/60/61	33-3/16	29-1/8	29-1/8



Specification

MODEL	BAH5-24-15
ELECTRICAL DATA	
Voltage / Phase (60 Hz)	208/230 / 1
Min. / Max. Voltage	187/253
MCA	15.5
MOP	24
COMPRESSOR	
Type	Scroll
Stage	Single
RLA	8
LRA	52
Crankcase Heater	Yes
CONDENSER COIL	
Throttle Type	Tube & Fin
Tube Size(O.D)	3/16
FAN MOTOR	
Motor Type	ECM
Horsepower (HP)	1-1/6
Full Load Amps (FLA)	1.6
REFRIGERATION SYSTEM	
Liquid Valve Size (O.D.)	3/8
Suction Valve Size (O.D.)	3/4
Liquid Line Size ("O.D.)	3/8
Suction Line Size ("O.D.)	3/4
Refrigerant Charge (lbs. - oz.)	6 LBS.-7 OZ
Superheat(°F)	9
OPERATION RANGE	
Cooling(°F)	55-115
Heating(°F)	5-86
SOUND POWER (DB)	74

Outdoor Unit	Indoor Unit		Cooling Capacity(btu/h)	EER2	SEER2	Heating Capacity(btu/h)	HSPF2
BAH5-24-15	AC5-3036A	CG80-040A	23200	11.70	14.30	22400	7.50
BAH5-24-15	AC5-3036A	CG80-060A	23200	11.70	14.30	22400	7.50
BAH5-24-15	AC5-3036B	CG80-060B	23200	11.70	14.30	22400	7.50
BAH5-24-15	AC5-3036B	CG80-080B	23200	11.70	14.30	22400	7.50
BAH5-24-15	AC5-3036C	CG80-080C	23200	11.70	14.30	22400	7.50
BAH5-24-15	AC5-3642B	CG80-060B	23600	11.70	14.30	22600	7.50
BAH5-24-15	AC5-3642B	CG80-080B	23600	11.70	14.30	22600	7.50
BAH5-24-15	AC5-3642C+TXV	CG80-080C	23400	12.00	15.20	22600	7.80
BAH5-24-15	AC5-3036A+TXV	96M060B3B	23000	11.70	14.30	22200	7.50
BAH5-24-15	AC5-3036A+TXV	96M080B3B	23000	11.70	14.30	22200	7.50
BAH5-24-15	AC5-3036B+TXV	96M060B3B	23000	11.70	14.30	22200	7.50
BAH5-24-15	AC5-3036B+TXV	96M080B3B	23000	11.70	14.30	22200	7.50
BAH5-24-15	AC5-3036C+TXV	96M080C4B	23000	11.70	14.30	22200	7.50
BAH5-24-15	AC5-3642B	96M060B3B	23400	11.70	14.30	22400	7.50
BAH5-24-15	AC5-3642B	96M080B3B	23400	11.70	14.30	22400	7.50
BAH5-24-15	AC5-3642C	96M080C4B	23400	11.70	14.30	22400	7.50
BAH5-24-15	CHX24CD	/	23000	11.70	14.30	23000	7.50
BAH5-24-15	CWM5-24-15	/	23000	11.70	14.30	23000	7.50
BAH5-24-15	CWM5-30-15	/	24000	12.00	15.20	24000	7.80
BAH5-24-15	LCM5-24-15+TXV	/	23200	11.70	14.30	22800	7.50
BAH5-24-15	LCM5-36-15+TXV	/	23400	12.00	15.20	22800	7.80
BAH5-24-15	LUC5-24-15	/	23000	11.70	14.30	22800	7.50
BAH5-24-15	LUC5-36-15+TXV	/	23000	11.70	14.30	22800	7.50



12201 N W 107th Avenue
Miami, FL 33178
1.866.524.9898 Toll Free
305.500.9898 Office
305.500.9896 Fax
<http://www.comfortstarusa.com>



The AHRI mark indicates Comfortstar participating in the AHRI Certification program. Visit ahridirectory.org for verification of individual certified products. Comfortstar reserves the right to change design and specs without notice. Comfortstar has a policy of update the data continuously. We are committed to using environmentally conscious print practices.

BAH5-24-15 14th Nov. 2023
Supersedes BAH5-24-15 (Nov.2023)

© 2023 ComfortStar