



Submittal

Split System Cooling

CC-FTA036-1S


Location: _____
Engineer: _____
Submitted to: _____
Submitted by: _____
Reference: _____

Approval: _____
Date: _____
Construction: _____
Unit # : _____
Drawing # : _____



Note: "Graphics in this document are for representation only. Actual model may differ in appearance."

Unit dimension



Model	Body dimension (mm)		
	A	B	C
CC-FTA030-1S	549	419	1853
CC-FTA036-1S	549	419	1853
CC-FTA048-1S	648	406	1922
CC-FTA060-1S	648	406	1922

Specification

Comfortstar Model			CC-FTA036-1S
Power supply			220-240V/1N/50Hz
Capacity	Cooling	kW	10
	Heating	kW	11
Max. Power Input		kW	100
Max. Current		A	0.9
Fan motor	Model		DR-310-170-8
	Type		DC
	Brand		OCEAN
	Capacitor		-
	Speed (Rated)	r/min	500/460/400
Indoor coil	Number of rows		3
	Fin type		Hydrophilic
	Tube diameter and type	mm	Φ7
Air flow (High speed)		m ³ /h	1400
Sound pressure level		dB(A)	47/45/41
Body	Dimension (W×H×D)	mm	549×1853×419
	Packing (W×H×D)	mm	645× 1960×510
	Net/Gross weight	kg	52/62
Refrigerant type			R410A
Throttle type			EXV
Design pressure		MPa	4.5
Liquid pipe / Gas pipe		mm	9.52/15.88
Connecting wire	Power wire	mm ²	2.5*2+2.5(below20m)4*2.5+2.5(below50m)
	Signal wire	mm ²	0.75*2 (2-core shielded wire)
Drainage water pipe (Outer diameter)		mm	20
Controller	Standard		Remote controller
	Optional		Wired controller
Operation temp		°C	16~32

ComfortStar®

12201 N W 107th Avenue
Miami, FL 33178
1.866.524.9898 Toll Free
305.500.9898 Office
305.500.9896 Fax
<http://www.comfortstarusa.com>



The AHRI mark indicates Comfortstar participating in the AHRI Certification program. Visit ahridirectory.org for verification of individual certified products. Comfortstar reserves the right to change design and specs without notice. Comfortstar has a policy of update the data continuously. We are committed to using environmentally conscious print practices.