



Submittal

Split System Cooling

CC-VAH008-3PS1


Location: _____
Engineer: _____
Submitted to: _____
Submitted by: _____
Reference: _____

Approval: _____
Date: _____
Construction: _____
Unit # : _____
Drawing # : _____



Note: "Graphics in this document are for representation only. Actual model may differ in appearance."

Unit dimension



	Dimension (mm)		
	W	H	D
CC-VAH008-3PS1	990	1740	840
CC-VAH010-3PS1	990	1740	840
CC-VAH012-3PS1	990	1740	840
CC-VAH014-3PS1	1340	1740	840
CC-VAH016-3PS1	1340	1740	840
CC-VAH018-3PS1	1340	1740	840
CC-VAH020-3PS1	1340	1740	840
CC-VAH022-3PS1	1340	1740	840
CC-VAH024-3PS1	1990	1740	840
CC-VAH026-3PS1	1990	1740	840
CC-VAH028-3PS1	1990	1740	840
CC-VAH030-3PS1	1990	1740	840
CC-VAH032-3PS1	1990	1740	840

ComfortStar®

Specification

Comfortstar model			CC-VAH008-3PS1
Cooling	Capacity	HP	8HP
		kW	25.2
	Rated current	A	9.04
	EER	W/W	4.75
Heating	Capacity	kW	27.4
	Rated current	A	8.93
	COP	W/W	5.5
Max. input consumption		kW	13.4
Max. current		A	23.1
DC Inverter compressor	Quantity		1
	Type		Scroll Compressor
	Brand		HITACHI
	Running frequency range	Hz	45~420
	Rotate speed range	rps	15~140
	Crankcase heater	W	35
Fan motor	Type		DC
	Model		DR-310-750-8-1
	Insulation class		B
	Rated speed	rpm	840
	Power output	W	750
Fan blade	Type		Axial
	Air flow	m ³ /h	11000
Refrigerant	Type		R410a
	Volume	kg	9
	Throttle type		EXV
Dimension (W*H*D)	Net	mm	990*1740*840
	Packing	mm	1060×1900×910
Weight	Net /Gross	kg	228/240
Outdoor sound level		dB(A)	58
Maximum operating pressure		MPa	4.5
Pipe size	Liquid pipe/Gas pipe	mm	Ø12.7/Ø22.2
Max. pipe length	Total pipe length	m	1000
	From OU to farthest IU(Actual length)	m	200
	From OU to farthest IU(Equivalent length)	m	240
	From 1st indoor distributor to farthest IU	m	40/90
Max. vertical length	Between OU & IU(OU above IU)	m	100
	Between OU & IU(OU below IU)	m	110
	Between IUs	m	40
	Between OUs	m	0
Cooling	Outdoor side/Indoor side	°C	-5~55/16~32
Heating	Outdoor side/Indoor side	°C	-30~30/16~32

ComfortStar®

12201 N W 107th Avenue
Miami, FL 33178
1.866.524.9898 Toll Free
305.500.9898 Office
305.500.9896 Fax
<http://www.comfortstarusa.com>



The AHRI mark indicates Comfortstar participating in the AHRI Certification program. Visit ahridirectory.org for verification of individual certified products. Comfortstar reserves the right to change design and specs without notice. Comfortstar has a policy of update the data continuously. We are committed to using environmentally conscious print practices.

CC-VAH008-3PS1 11th April 2023
Supersedes CC-VAH008-3PS1 Apr.2023)

© 2023 ComfortStar