

Air Handler Heat Pump System			
Location:		Approval:	
Engineer:		Date:	
Submitted to:		Construction:	
Submitted by:		Unit #:	
Reference:		Drawing #:	



INDOOR SPECIFICATION			
Indoor Air Flow (High/Low) (CFM)		965/766	
Indoor Noise Level (High/Low) (dBA)		49	
Dimension (W×D×H)	inch	22-3/64×19-3/32×39-9/16	
	mm	560×485×1005	
Package (W×D×H)	inch	24-21/64×21-9/64×42-53/64	
	mm	620×538×1085	
Net/Gross Weight	lbs	88/95	
	kg	39.9/43.1	

OUTDOOR SPECIFICATION			
Compressor Type		TWIN-ROTARY	
Compressor Model		KTM240D57UMT	
Refrigerant		R32	
Refrigerant Oil Charge(mL)		670	
Refrigerant Oil		VG74	
Outdoor Air Flow (Max) (CFM)		2800.0	
Outdoor Noise Level (dBA)		59	
Dimension (W×D×H)	inch	29-9/64×29-9/64×25	
	mm	740×740×635	
Package (W×D×H)	inch	30-5/16×30-5/16×26-3/16	
	mm	770×770×665	
Net/Gross Weight	lbs	140/148	
	kg	63.5/67	

EFFICIENCY			
Cooling		Heating	
SEER2	15.0	HSPF2-5	7.2
EER2	9.5	COP	3.50


PERFORMANCE of Cooling	
Cooling (Btu/hr)	
Rated Capacity	30000
Min/Max Capacity	9800~32000
Moisture Removal(L/h)	3.1
Standard Operating Range(*F/*C)	5~131(-15~55)
Rated Cooling Conditions:	
Indoor: 80°F DB/67°F WB	
Outdoor: 95°F DB/75°F WB	

PERFORMANCE of Heating	
Heating (Btu/hr)	
1. @ 47°F Rated	31000
2. @ 47°F Min/Max Capacity	11500~34000
3. @ 17°F Rated	16000
4. @ 5°F Rated: Capacity / COP	20000/1.9
5. @ 5°F Max: Capacity	23000
Standard Operating Range(*F/*C)	-4~75(-20~24)
1. Rated Heating Conditions:	
Indoor: 70°F DB/60°F WB	
Outdoor: 47°F DB/43°F WB	
2. Rated Heating Conditions:	
Indoor: 70°F DB/60°F WB	
Outdoor: 17°F DB/15°F WB	
3. Heating Conditions, Compressor	
Indoor: 70°F DB/60°F WB	
Operating at Max. Frequency	
Outdoor: 5°F DB/5°F WB	

ELECTRICAL	
Indoor Power Supply	208/230V,60Hz,1Ph
Indoor MCA 115V/(208/230V)	2.8
Indoor MOP	3
Outdoor Power Supply	208/230V,60Hz,1Ph
Outdoor MCA	22.5
Outdoor MOP	25
Communication Wiring	AWG 25×3 Shielded
Compressor RLA	9.45
Outdoor Fan Motor RLA	2.3
Outdoor Fan Motor W	200
Indoor Fan Motor RLA	2.23
Indoor Fan Motor W	220
System Power Input @ Cooling (W)	3157.89473684211(400~3200)
System Power Input @ Heating (W)	2700(550~3250)
MCA: Min. circuit amps (A)	MOCP: Max. over current protection (A)
RLA: Rated load amps (A)	W: Fan motor rated output (W)


PIPING	
Throttle type(Indoor)	Piston
Throttle type(Outdoor)	Capillary
Liquid Size	9.52mm(3/8in)
Gas Size	19mm(3/4in)
Max. Piping Length(ft/m)	164(50)
Max. Height Difference(ft/m)	82(25)
Max. Pre-charged Length(ft/m)	24.6(7.5)
Refrigerant Pre-charged Amount(oz/kg)	102.29(2.9)
Additional Charge of Refrigerant((oz/ft)/(g/m))	0.52(48)
Connection Method	Flared

Indoor Unit Dimension




Dimensions \ Model		18/24K		24/36K	
		inch	mm	inch	mm
A	Model Height	36-1/32	915	39-9/16	1005
B	Model width	20-15/32	520	22-3/64	560
C	Supply Air Opening width	14-61/64	380	19-3/32	485
D	Return Air Opening Width	17-33/64	445	18-57/64	480
E	Model Depth	9-29/64	240	9-27/32	250

Outdoor Unit Dimension




Dimensions \ Model		18K/24K		30K/36K	
		inch	mm	inch	mm
W	Model width	23-5/8	600	29-9/64	740
L	Model length	23-5/8	600	29-9/64	740
H	Model height	25	635	25	635
A	Liquid side valve height	2-31/64	63	2-31/64	63
B	Distance between two valves	3-1/32	77	3-1/32	77
C	Gas side valve height	2-9/32	58	2-9/32	58

Installation Instruction For Outdoor Unit



Fan Performance For Indoor Unit



Features

- Front air intake, easy installation
- External static pressure up to 0.80 In.W.G
- 1 inch R4.2 fiberglass free insulation reduces condensation and boosts efficiency(optional)
- Optional Auxiliary heat kit up to 20kW
- Easy Maintenance
- Multiple control options available:
 - Wired controller with built-in WiFi
 - Third-Party 24V Thermostat
- Adaptive Control System
- Crankcase heater equipped as standard