

Air Handler Heat Pump System

Location:	Approval:
Engineer:	Date:
Submitted to:	Construction:
Submitted by:	Unit #:
Reference:	Drawing #:



INDOOR SPECIFICATION

Indoor Air Flow (High/Low) (CFM)	830/420
Indoor Noise Level (High/Low) (dBA)	42/38
Dimension (W×D×H)	inch 17-33/64×21-1/32×45
	mm 445×534×1143
Package (W×D×H)	inch 20-55/64×26-37/64×46-17/64
	mm 530×675×1175
Net/Gross Weight	lbs 114/127
	kg 51.5/57.5

OUTDOOR SPECIFICATION

Compressor Type	ROTARY
Compressor Model	KTM240D57UMT
Refrigerant	R32
Refrigerant Oil Charge(mL)	670
Refrigerant Oil	VG74
Outdoor Air Flow (Max) (CFM)	2000.0
Outdoor Noise Level (dBA)	55
Dimension (W×D×H)	inch 36-1/32×25-19/32×13-37/64
	mm 915×650×345
Package (W×D×H)	inch 40-5/32×28-15/16×17-1/8
	mm 1020×735×435
Net/Gross Weight	lbs 84/92
	kg 42/45.5

EFFICIENCY

Cooling		Heating	
SEER2	17.7	HSPF2	8.5
EER2	10.4	COP	3.40

PERFORMANCE of Cooling

Cooling (Btu/hr)	
Rated Capacity	24000
Min/Max Capacity	7200~27000
Standard Operating Range(*F/°C)	5~131(-15~55)
Rated Cooling Conditions: Indoor: 80°F DB/67°F WB Outdoor: 95°F DB/75°F WB	

PERFORMANCE of Heating

Heating (Btu/hr)	
1. @ 47°F Rated	26000
2. @ 47°F Min/Max Capacity	7100~30000
3. @ 17°F Rated	15900
4. @ 5°F Rated: Capacity	20000
Standard Operating Range(*F/°C)	-4~75(-20~24)
1. Rated Heating Conditions: Indoor: 70°F DB/60°F WB Outdoor: 47°F DB/43°F WB	
2. Rated Heating Conditions: Indoor: 70°F DB/60°F WB Outdoor: 17°F DB/15°F WB	
3. Heating Conditions, Compressor Operating at Max. Frequency Indoor: 70°F DB/60°F WB Outdoor: 5°F DB/5°F WB	


ELECTRICAL

Indoor Power Supply	208/230V, 60Hz, 1Ph
Indoor MCA 115V/(208/230V)	3.5
Indoor MOP	6
Outdoor Power Supply	208/230V, 60Hz, 1Ph
Outdoor MCA	20
Outdoor MOP	25
Communication Wiring	AWG 25×3 Shielded
Compressor RLA	9.45
Outdoor Fan Motor RLA	2
Outdoor Fan Motor W	75
Indoor Fan Motor RLA	2.6
Indoor Fan Motor W	249
System Power Input @ Cooling (W)	2308(530 ~ 2870)
System Power Input @ Heating (W)	2265(440 ~ 2730)
MCA: Min. circuit amps (A)	MOC: Max. over current protection (A)
RLA: Rated load amps (A)	W: Fan motor rated output (W)

PIPING


Throttle type(Indoor)	Piston
Throttle type(Outdoor)	Capillary
Liquid Size	9.52mm(3/8in)
Gas Size	19mm(3/4in)
Max. Piping Length(ft/m)	164(50)
Max. Height Difference(ft/m)	82(25)
Max. Pre-charged Length(ft/m)	24.6(7.5)
Refrigerant Pre-charged Amount(oz/kg)	58.2(1.65)
Additional Charge of Refrigerant((oz/ft)/(g/m))	0.52(48)
Connection Method	Flared

Indoor Unit Dimension




Dimensions		Model	18K/24K		30K/36K		48K/60K	
			inch	mm	inch	mm	inch	mm
A	Model Height		45-3/4	1162	49-49/64	1264	53-47/64	1365
B	Model width		17-41/64	448	21-9/64	537	24-39/64	625
C	Supply Air Opening width		15-5/8	397	19-9/64	486	22-19/32	574
D	Return Air Opening Width		15-25/64	391	18-47/64	476	22-23/64	568
E	Model Depth		21-7/64	536	21-7/64	536	21-7/64	536
F	Supply Air Opening Depth		10-9/32	261	10-9/32	261	10-9/32	261
G	Return Air Opening Depth		18-23/32	475.5	18-23/32	475.5	18-23/32	475.5
H	Supply Air Opening Clearance		15/16	24	15/16	24	15/16	24
I	Return Air Opening Side Clearance		1-1/8	28.5	1-1/8	28.5	1-1/8	28.5
J	Return Air Opening Front Clearance		1-21/32	42	1-21/32	42	1-21/32	42
K	Return Air Opening Back Clearance		45/64	18	45/64	18	45/64	18

Outdoor Unit Dimension




Dimensions \ Model		18K/24K		30K/36K/48K/60K	
		inch	mm	inch	mm
W	Model width	915	36-1/32	965	37-63/64
H	Model height	650	25-19/32	810	31-57/64
A	Distance between left and right foot bolts	605	23-13/16	635	25
B	Distance between front and rear foot bolts	357	14-1/16	405	15-15/16
D	Model depth	392	15-7/16	448	17-41/64

Installation Instruction For Outdoor Unit



Fan Performance For Indoor Unit



Features

- High efficiency and energy-saving, SEER2 up to 18.4
- Multi-position installation: horizontal(left or right), vertical(up or down)
- ECM fan motor with constant torque technology
- External static pressure up to 0.80 In.W.G
- 1 inch R4.2 fiberglass free insulation reduces condensation and boosts efficiency(optional)
- Optional Auxiliary heat kit up to 20kW
- Easy Maintenance
- Multiple control options available:
 - Wired controller with built-in WiFi
 - Third-Party 24V Thermostat
- Adaptive Control System
- Crankcase heater equipped as standard