

ComfortStar® SUBMITTAL DATA SHEET

36000Btu/h	A-Coil
Location: _____ Engineer: _____ Submitted to: _____ Submitted by: _____ Reference: _____	Approval: _____ Date: _____ Construction: _____ Unit #: _____ Drawing #: _____


Set Model	
Indoor unit model	AC32-36C-15
Outdoor unit model	BAH32-36-15(309)
Certified AHRI ETL	



SYSTEM PERFORMANCE DATA		
Power supply		
Normal Operational Volt	(V, Ph, Hz)	220-230V, 1Ph, 60Hz
Voltage Range	(V)	187-253
Electrical		
Minimum circuit ampacity	(A)	25.0
Max.fuse	(A)	30.0
Cooling		
Rated Capacity	(Btu/h)	36000
Capacity Range	(Btu/h)	13000~38000
Power Input	(W)	3529
Rated current	(A)	15.98
SEER2	(Btu/W)	14.3
EER	(Btu/W)	10.2
Heating at 47F		
Rated Capacity	(Btu/h)	36000
Capacity Range	(Btu/h)	11000~39000
Power Input	(W)	3200
Rated current	(A)	14.20
HSPF4	(Btu/W)	8.5
HSPF5	(Btu/W)	6.9
COP	W/W	3.4
Heating at 5F		
Capacity	(Btu/h)	26000
COP	W/W	1.8
REFRIGERANT PIPE DATA		
Design pressure	(PSIG)	609/174
Refrigerant Type		R32
Refrigerant charge	(oz)	102.3
Additional charge	(oz/ft)	0.5
	(g/m)	48.0
Liquid side/ Gas side	(inch)	3/8" / 3/4"
	(mm)	Φ9.52 / Φ19
Max. pipe length	(ft)	246.0
	(m)	75.0
Max. difference in level	(ft)	98.4
	(m)	30.0
Connection method	Indoor	Braze
	Outdoor	Flared to braze
Indoor(cooling)	(Deg. °F / °C)	60~90 / 16~32
Indoor(heating)	(Deg. °F / °C)	60~90 / 16~32
Outdoor(cooling)	(Deg. °F / °C)	5~131 / -15~55
Outdoor(heating)	(Deg. °F / °C)	-4~75 / -20~24


INDOOR UNIT DATA		
Throttle		TXV for Cooling
Indoor fan motor		
Type		---
Model		---
Qty		---
Input	(W)	---
RLA	(A)	---
LRA	(A)	---
Capacitor	(uF)	---
Speed(Hi/Mi/Lo)	(r/min)	---
Air flow & Noise level		
Indoor air flow (Hi/Med/Lo)	(CFM)	---
Indoor noise level (Hi/Med/Lo)	[dB(A)]	---
Dehumidification		
	(Pint/H)	---
Indoor unit		
Dimension (WxDxH)	(inch)	21-1/32*21-1/32*23-37/64
	(mm)	534*534*599
Packing(WxDxH)	(inch)	24-1/64*26-49/64*26-63/64
	(mm)	610*680*660
Net/Gross weight	(lbs.)	64/74
	(kg)	29.2/33.6
OUTDOOR UNIT DATA		
Compressor		
Type		KTM240D57UMT
Model		Twin-ROTARY
Brand		GMCC
Capacity	(Btu/h)	27095.1
Input	(W)	2085
Rated current (RLA)	(A)	9.45
Refrigerant oil/oil charge	(ml)	ESTER OIL VG74 670
Throttle		Capillary for heating
Outdoor fan motor		
Model		DQ-DRN-310-200-8-B(A)
Qty		1
Input	(W)	200.00
RLA	(A)	0.92
Air flow & Noise level		
Outdoor air flow (Max.)	(CFM)	2800
Outdoor noise level	[dB(A)]	59.0
Outdoor unit		
Dimension (W×D×H)	(inch)	29-9/64×29-9/64×25
	(mm)	740×740×635
Packing (W×D×H)	(inch)	30-5/16×30-5/16×26-3/16
	(mm)	770×770×665
Net/ Gross weight	(lbs.)	140/148
	(kg)	63.5/67

Indoor unit dimension



Model	Dimension(inch)			Drain hole	
	W	D	H	L1	L2
AC32-18B-15 AC32-24B-15	17-33/64	21-1/32	17-63/64	Main drain hole	Overflow drain hole
AC32-30B-15 AC32-36B-15	17-33/64	21-1/32	23-37/64		
AC32-30C-15 AC32-36C-15	21-1/32	21-1/32	23-37/64		
AC32-48C-15 AC32-60C-15	21-1/32	21-1/32	27-51/64		
AC32-48D-15 AC32-60D-15	24-31/64	21-1/32	27-51/64		

Outdoor unit dimension



Dimensions \ Model		18K/24K		30K/36K		48K/60K	
		inch	mm	inch	mm	inch	mm
W	Model width	23-5/8	600	29-9/64	740	29-9/64	740
L	Model length	23-5/8	600	29-9/64	740	29-9/64	740
H	Model height	25	635	25	635	32-7/8	835
A	Liquid side valve height	2-31/64	63	2-31/64	63	2-31/64	63
B	Distance between two valves	3-1/32	77	3-1/32	77	3-1/32	77
C	Gas side valve height	2-9/32	58	2-9/32	58	2-9/32	58