

ComfortStar®

Air Conditioning & Heating Products



ComfortStarX³²

CAC-WI Series
INVERTER **Wi-Fi**



HIGH EFFICIENCY - COOLING DUCTLESS MINI-SPLIT SYSTEMS

FEATURES:

- Triple-Layer Anti-Rust Protection
- Gold Fin
- T-shaped Top Cover Design
- Wide-Range Voltage Operation
- ECO Mode
- Cooling-High Efficiency Tube
- i-Clean
- WiFi (Optional)



Wi-Fi



Sleep
Mode



High
Quality



Auto
Restart



Noise
Reduction

Comfort, it's in our name.



📍 12860 N.W. South River Dr. | Medley, FL 33178

📞 **Toll Free:** 1-866-524-9898 | **Phone:** 1-305-500-9898 | **Fax:** 1-305-500-9896 **Email us:** info@comfortstarusa.com ✉️

www.comfortstarusa.com 🌐

CAC-WI Series
INVERTER **Wi Fi**

UP TO
22 SEER2



Indoor Unit			CAC12CA(I)-WI	CAC12CD(I)-WI	CAC18CD(I)-WI	CAC24CD(I)-WI	CAC6CD(I)-WI
Outdoor Unit			CAC12CA(O)-WI	CAC12CD(O)-WI	CAC18CD(O)-WI	CAC24CD(O)-WI	CAC36CD(O)-WI
Power Supply		V-Ph-Hz	115V_1Ph, 60HZ	220_230V_1Ph, 60HZ	220_230V_1Ph, 60HZ	220_230V_1Ph, 60HZ	220_230V_1Ph, 60HZ
Cooling (Standard Conditions)	Capacity	Btu/h	12000	12000	17500	22000	33000
	Range		2050~13480	2050~14010	4100~18800	5300~23900	8300~36900
	Input	W	1000	1000	1522	1913	2900
	Range		160~1290	160~1410	150~1600	115~2180	340~3500
	Current	A	11.5	4.7	6.7	9.0	12.90
	Range		2.1~13.6	2.1~6.3	0.7~7.1	1.0~9.5	1.5~15.5
	EER2	W/W	12.0	12.0	11.5	11.5	11.4
	SEER2	Btu/W	22.0	21.0	22.0	20.5	21.0
Rated Power Input		W	1650	2160	3000	3450	5300
Rated Current		A	17.0	10	14.0	16.0	24.0
Starting Current		A	/	/	/	/	/
Indoor Air Flow (Hi/Mi/Lo)		CFM	382/324/294	382/324/294	471/353/306	588/471/400	
Indoor Noise Level (Hi/Mi/Lo)		dB(A)	43/38/36	43/38/36	45/40/30	48/41/33	49.5/42/38
Indoor Unit	Dimension (W*D*H)	In.	31.6x7.9x11.6	31.6x7.9x11.6	38.2x9.0x12.6	42.6x9.2x13.3	49.6X11.1X14.3
	Packing (W*D*H)	In.	34.4x11.2x14.76	34.4x11.2x14.76	41.1x12.0x15.9	45.5x16.3x12.4	52.8X17.7X15.0
	Net/Gross Weight	Lbs.	18.1/24.69	18.1/24.69	24.3/32.63	29.3/38.36	42.1/55.6
Outdoor Air Flow		CFM	1059	1059	1235	1471	1471
Outdoor Noise Level		dB(A)	54	54	54	59	60
Outdoor Unit	Dimension (W*D*H)	In.	28.3x10.6x19.5	28.3x10.6x19.5	30.1x11.9x21.9	31.7x13.0x21.8	37.2X16.1X31.9
	Packing (W*D*H)	In.	33.15x14.06x21.65	33.15x14.06x21.65	34.84x14.76x23.82	37.01x16.14x23.82	42.9X19.7X34.5
	Net/Gross Weight	Lbs.	45.2/53.35	42.6/50.71	51.8/60.85	61.1/72.53	123.9/142.0
Refrigerant Type		oz	R32/17.7	R32/17.7	R32/21.9	R32/26.5	R32/63.5
Design Pressure		PSI	624/247	624/247	624/247	624/247	624/247
Refrigerant Piping	Liquid Side	In.	1/4"	1/4"	1/4"	3/8"	3/8"
	Gas Side	In.	3/8"	3/8"	1/2"	5/8"	5/8"
	Max. Refrigerant Pipe Length	In.	984	984	1181	1181	1969
	Max. Difference In Level	In.	394	394	787	787	984
Connection Wiring			16#x4	16#x4	16#x4	16#x4	14#X4
Plug Type			no-plug	no-plug	no-plug	no-plug	no-plug
Thermostat Type			Remote Control	Remote Control	Remote Control	Remote Control	Control Remoto
Operation Temperature		°F	63~86	63~86	63~86	63~86	63~86
Indoor Temperature		°F	63~90	63~90	63~90	63~90	63~90
Outdoor Temperature		°F	34~122	34~122	34~122	34~122	34~122
Application Area (Cooling Standard)		ft²	161.4~236.7	161.4~236.7	258.2~376.6	312.0/462.7	473.6~688.9
Qty'per 20' /40' /40'HQ			130/276/302	130/276/302	88/186/220	78/168/194	38/80/96

ComfortStar®
Air Conditioning & Heating Products



Comfort, it's in our name.