

ComfortStar®

Air Conditioning & Heating Products



Light Commercial Rooftop Package Unit

208/230V, 3Ph, 60Hz

Model: CRT7-120TT

ComfortStar®

Address: 12201 N W 107th Avenue Miami, FL 33178
1.866.524.9898 Toll Free
305.500.9898 Office
305.500.9896 Fax
<http://www.comfortstarusa.com>



Submittal Data Sheet

Light Commercial Rooftop Package Unit Capacity:10Ton

Model (AC)			CRT7-120TT
Power Supply			208/230V~60HZ,3Ph
Cooling Capacity		KBtu/h	114
		kW	33.4
Power Input		kW	10.18
EER		Btu/h/W	11.2
Max.input consumption		W	12,800
Max.current		A	43
Indoor fan air flow		CFM	3,600
ESP		in.wg/Pa	0-250
Outdoor Sound Rating(BELS)			8.2
Compressor	Type		Scroll
	Quantity		2
Indoor coil			Micro-channel
Outdoor coil			Micro-channel
Indoor fan	Type		Centrifugal
	Drive type		Belt
	Quantity		1
Outdoor fan	Type		Axial
	Drive type		Direct
	Quantity		2
Refrigerant Type			R454B
Refrigerant Volume	Circle A/B	lbs	5.07/4.41
Filters	Type Furnished		Disposable
	Number Size Recommended		(4)20*20*2
Operation Ambient Temperature		°F	0-125
Net Dimensions(W×H×D)		inch	88.6×48.8×59.1
Packing Dimensions(W×H×D)		inch	89.4×50.2×59.6
Loading Quantity per 20GP/40GP/40HC			3/7/14
Standard motor (weight)			
Unit weight(lb)			985(447kg)
Shipping Weight(lb)			1047(475kg)
Standard motor (weight)			
Unit weight(lb)			983(446kg)
Shipping Weight(lb)			1045(474kg)
Oversize motor(weight)			
Unit weight(lb)			990(449kg)
Shipping Weight(lb)			1052(477kg)


Features:

- Wide operating range:
Cooling Ambient temp.: -0°F~125°F
Heating Ambient temp.: -40°F~86°F
- ETL and AHRI certification
- Dual-stage, High efficiency compressor
- DC outdoor Motor
- VFD+pulley design
- Micro-channel heat exchanger
- High static, Oversize motor model can be customized
- Electric heater optional
- Condensation water flow switch option
- High attitude kit option 7-speed fan control.
- Compatible with local 24V wired controller
- Horizontal/vertical air duct connect
- Multi-function PCB, LED display, Error code showing
- Compatible with field accessory: Curb/Economizer/Hail guard



Dimensions:

(Unit: in(mm))


Units — overview



Units — front and side views (in inches)




Units — bottom view (in inches)




NOTES:

1. THROUGH THE BASE GAS AND ELECTRICAL IS NOT STANDARD ON ALL UNITS.
2. VERIFY WEIGHT, CONNECTION, AND ALL DIMENSION WITH INSTALLER DOCUMENTS BEFORE INSTALLATION.


Foundation units — back view (horizontal configuration) (in inches)



Downflow unit clearance (in inches)



Roof curb (in inches)



Installation Space Requirements:

(Unit: inch)

